



BK3V-STS | P/C HD ST STD-STD BLACK 3'

Body Features

Color	Black
Conductor Plating	Gold

Configuration Features

Number of Connectorized Ends	2
------------------------------	---

Contact Features

Center Contact Plating	Gold
------------------------	------

Dimensions

Cable Assembly Length	0.93 m 3.051 ft
-----------------------	-------------------

Electrical Characteristics

Connector Impedance	75 ohm
Impedance	75 ohm
Voltage	600 V

Operation/Application

For Use With	All Standard Size 2x24 and 2x26 Panels
--------------	--

Product Availability

Region	North America
Applicable Country	Not Specified

Product Type Features

Product Type	Cable Assembly
Assembly Type	WECO ST Standard Size ST HD to Standard Size Plug
Connector Type (End A)	ST Plug
Connector Type (End B)	ST Plug
Cable Assembly Type	ST Plug to ST Plug
Cable Type	Coaxial
Coaxial Cable Type	RG 59
Product Category	Broadcast Video
Product Designation	Patch Cord
Product Line	Broadcast
RF Connector Type	Video Jacks

BK3V-ST5 | P/C HD ST STD-STD BLACK 3'

Shielded Yes

Usage Conditions

Operating Temperature Range -40 – 65 °C

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant