



BK3V-STS | P/C HD ST STD-STD BLACK 3'

## Body Features

|                   |       |
|-------------------|-------|
| Color             | Black |
| Conductor Plating | Gold  |

## Configuration Features

|                              |   |
|------------------------------|---|
| Number of Connectorized Ends | 2 |
|------------------------------|---|

## Contact Features

|                        |      |
|------------------------|------|
| Center Contact Plating | Gold |
|------------------------|------|

## Dimensions

|                       |                   |
|-----------------------|-------------------|
| Cable Assembly Length | 0.93 m   3.051 ft |
|-----------------------|-------------------|

## Electrical Characteristics

|                     |        |
|---------------------|--------|
| Connector Impedance | 75 ohm |
| Impedance           | 75 ohm |
| Voltage             | 600 V  |

## Operation/Application

|              |  |
|--------------|--|
| For Use With | All Standard Size 2x24 and 2x26 Panels |
|--------------|--|

## Product Availability

|                    |               |
|--------------------|---------------|
| Region             | North America |
| Applicable Country | Not Specified |

## Product Type Features

|                        |   |
|------------------------|---|
| Product Type           | Cable Assembly                                    |
| Assembly Type          | WECO ST Standard Size ST HD to Standard Size Plug |
| Connector Type (End A) | ST Plug   |
| Connector Type (End B) | ST Plug   |
| Cable Assembly Type    | ST Plug to ST Plug                                |
| Cable Type             | Coaxial   |
| Coaxial Cable Type     | RG 59   |
| Product Category       | Broadcast Video                                   |
| Product Designation    | Patch Cord  |
| Product Line           | Broadcast   |
| RF Connector Type      | Video Jacks                                       |

BK3V-ST5 | P/C HD ST STD-STD BLACK 3'

Shielded Yes

## Usage Conditions

Operating Temperature Range -40 – 65 °C

## Regulatory Compliance/Certifications

### Agency

RoHS 2011/65/EU

### Classification

Compliant