



MicroFlex Wire and Cable
 Home
 About Us
 Products
 Capabilities

• [Contact Us](#)




SILICONE Insulated Extra Flexible Hookup wire

- Very Flexible Bare or Plated copper conductor with 0.020 mil Wall of Flexible -65° to 200°C oil and acid resistant SILICONE Rubber

	Specific Gravity	Temp. Range	Dielectric Constant	Volt Break Per mil	Flexibility	Abbrasion	Gasoline
Silicone	1.32	-65°- 200°	3	600	Excellant	Fair	Good

Colors Available



Also Available: GREEN with YELLOW Stripe for Ground

PART #	AWG	STRAND awg	COND DIA.	FINAL O.D	Resistance 20°C-68°F OHMS/MFT	Flexibility
BN3025SIL10	30	25/44awg	0.012	0.046	97.5	Very Flexible
BN2951SIL10	29	51/46awg	0.014	0.05	82.7	Very Flexible
BN2840SIL10	28	40/44awg	0.015	0.051	64.7	Very Flexible
BN2441SIL10	24	41/40awg	0.024	0.06	25.6	Extra Flexible
BN24105SIL10	24	105/44awg	0.024	0.06	27.2	Very Flexible
BN2265SIL10	22	65/40awg	0.031	0.068	16.1	Extra Flexible
BN2250SIL10	22	3×50/44awg	0.032	0.068	17.5	Very Flexible
BN2037SIL10	20	7×37/44awg	0.042	0.078	10	Very Flexible
BN1859SIL10	18	7×59/44awg	0.052	0.088	6.2	Very Flexible
BN1695SIL10	16	7×95/44awg	0.062	0.098	4	Very Flexible

If you do not see exactly what you are looking for, complete this request form and we will contact you about availability and pricing as quickly as possible.

Product and Sample Request Form

Your Name:

Email:

Phone:

Address: