

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: **AEES**

TOL Spec ID: **3/CF- 101112**
Customer Part Number: **709863**

Description: 3 Conductor Flat Cable with 3 /12 GA GXL Inners,
85 Deg C PVC Jacket with Print

Inners: **GXL-12-19-B (Lbl) / GXL-12-19-B (Red) / GXL-12-19-B (Brn)**

XLPE 125 Deg C Insulated Cable
Stranding: 19 x .0177" bare Lay = 2.0"
Insulation OD = .139" (min) / .143" (nom)

Outer Jacket: **PVC 85 Deg C Lead Free Compound**
(Pressure Extruded)

Jacket Color: Black
Max Height : 0.194 inches
Nom Height : 0.192 inches
Min Height : 0.190 inches
Max Width : 0.484inches
Nom Width : 0.481 inches
Min Width : 0.478 inches
Jacket Wall : .028" (Nom)
Max Runout: 0.008 inches
Surface Print: SAE GXL

Specification Reference Data

SAE: J1128	Ford: N/A	Chrysler: N/A
UL : N/A	CSA: N/A	Packard: N/A
Other: Navistar Part Number: PT08-34473		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Quality Engineer)

Date: 9-28-2011

Mat'l Spec Form (#F-0270)

Rev. 0

7-30-1998