

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: **AEES**

TOL Spec ID: **2/CF- 103414**
Customer Part Number: **457742**

Description: 2 Conductor Flat Cable with 2 /14 GA SXL Inners,
105 Deg C PVC Jacket with No Print

Inners: **SXL-14-19-B (Red) / SXL-14-19-B (Yel)**
XLPE 125 Deg C Insulated cable
Stranding: 19 x .0142" Bare lay = 1.5"
Insulation OD = .134" (min) / .142" (nom)

Outer Jacket: **PVC 105 Deg C Lead Free Compound**
(Pressure Extruded)

Jacket Color: Gray
Max Height : 0.201 inches
Nom Height : 0.199 inches
Min Height : 0.198 inches
Max Width : 0.343 inches
Nom Width : 0.340 inches
Min Width : 0.338 inches
Jacket Wall : .026" (Nom)
Max Runout: 0.008 inches
Surface Print: None

Specification Reference Data

SAE: J1128	Ford: N/A	Chrysler: N/A
UL : N/A	CSA: N/A	Packard: N/A
Other: FRTLNR P#48-023339-240		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By:
Date: 9-28-2011
Mat'l Spec Form (#F-0270)

Mir Hussain (Corporate Quality Engineer)

Rev. 0

7-30-1998