



# PRODUCT DATA SHEET


Controlled Document - Engineering Drive

1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** TBD  
**DESCRIPTION:** 14/4 SXL FLAT BRAKE CABLE  
**CONSTRUCTION:** This cable consists of four 14 AWG XLPE insulated conductors laided flat under an overall PVC jacket.  
**STYLE:** SAE J1128 SXL Jacketed Brake Cable

## Construction Parameters:

Conductors 14 AWG Bare Copper  
Stranding 19/27  
Insulation Material XLPE  
Insulation Thickness 0.035" Nom.  
Insulated Conductor Diameter 0.136" Nom.  
Number of Conductors 4  
Jacket Material PVC  
Jacket Thickness 0.036" Nom.  
Overall Cable Diameter 0.208" x 0.624" Nom.  
Approximate Cable Weight 117.3 Lbs/1M' Nom.



## Electrical Properties:

Temperature Rating Conductors 125C, Jacket 80C  
DC Resistance per Conductor @ 20°C 2.80 Ohms/1M' Nom.

Insulation Colors Brown Yellow Dark Green Dark Blue  
Jacket Color Black  
Legend (Surface Ink Print) No Print

This product complies with European Directive 2002/95/EC (RoHS)  
Material is not returnable and purchase order is non-cancelable after production has been started or special materials have been ordered.  
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name \_\_\_\_\_ Date Signed \_\_\_\_\_

Customer Approval \_\_\_\_\_

Specification Issue Date: October 21, 2009