



For more Information  
please call

1-800-Belden1



## General Description:

Surveillance, CATV & MATV Cable, RG6, Plenum-CMP & CATVP, 18 AWG solid bare copper, foamed FEP core, Duofoil®+90% aluminum braid, Flamarrest® jacket

## Usage (Overall)

Suitable Applications: CATV, MATV

## Physical Characteristics (Overall)

### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	18	Solid	BC - Bare Copper	.040

### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FFEP - Foam Fluorinated Ethylene Propylene	.170

### Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	AL - Aluminum	90

### Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

### Overall Cable

Overall Nominal Diameter: 0.233 in.

## Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 28 lbs/1000 ft.

Max. Recommended Pulling Tension: 104 lbs.

Min. Bend Radius/Minor Axis: 2.250 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP, CATVP

NEC Articles: 820

CEC/C(UL) Specification: CMP

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

## 633938 Coax - Commercial CATV or MATV Applications

MII Order #39 (China RoHS): Yes

RG Type: 6/U

Series Type: Series 6

### Flame Test

UL Flame Test: NFPA 262

C(UL) Flame Test: FT6

### Plenum/Non-Plenum

Plenum (Y/N): Yes

## Surface Printing (Overall)

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

75

### Nom. Inductance:

Inductance (µH/ft)

.097

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

16.3

### Nominal Velocity of Propagation:

VP (%)

83

### Nominal Delay:

Delay (ns/ft)

1.24

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

6.4

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

3.5

### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	0.24
3	0.45
5	0.55
8	0.70
10	0.85
50	1.50
100	2.1
200	3.1
400	4.5
700	6.0
900	6.9
1000	7.3

### Max. Operating Voltage - UL:

Voltage

300 V RMS

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
633938 008U1000	1,000 FT	29.000 LB	GRAY		RG-6/U PLENUM COAX
633938 009U1000	1,000 FT	29.000 LB	WHITE		RG-6/U PLENUM COAX
633938 010U1000	1,000 FT	29.000 LB	BLACK		RG-6/U PLENUM COAX
633938 877U1000	1,000 FT	29.000 LB	NATURAL		RG-6/U PLENUM COAX
633938 8771000	1,000 FT	29.000 LB	NATURAL	C	RG-6/U PLENUM COAX
633938 877500	500 FT	15.000 LB	NATURAL	C	RG-6/U PLENUM COAX

### Notes:

C = CRATE REEL PUT-UP.

## 633938 Coax - Commercial CATV or MATV Applications

Revision Number: 1    Revision Date: 03-11-2013

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).