

## 4794R Coax - 4K Ultra-High-Definition Coax Cable for 12G-SDI



For more Information  
please call

1-800-Belden1



### General Description:

12 GHz, 4K UHD Precision Video Cable, 75 Ohm, 16 AWG solid 0.051" silver-plated copper conductor, gas-injected foamed high-density polyethylene insulation, Duofoil® bonded to the core + tinned copper braid shield (95% coverage) plus Beldfoil® with shorting fold, PVC jacket.

### Usage (Overall)

Suitable Applications: SMPTE 2082-1 12 Gb/s UHD TV, SMPTE 2081-1 6 Gb/s UHD TV, SMPTE 424M 3 Gb/s HD-SDI 1080p

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	16	Solid	SPC - Silver Plated Copper	0.051

Total Number of Conductors: 1

#### Insulation

Insulation Material:

Insulation Material	Dia. (in.)
Gas-injected FHDPE - Foam High Density Polyethylene	0.225

#### Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)	Description
1	Bonded Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100.000	Bonded to insulation
2		Braid	TC - Tinned Copper	95.000	
3	Bonded Beldfoil® with shorting fold	Tape	Polyester Tape-Aluminum Foil	100.000	Bonded to jacket

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

#### Overall Cable

Overall Nominal Diameter: 0.320 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +75°C

Bulk Cable Weight: 59 lbs/1000 ft.

Max. Recommended Pulling Tension: 111 lbs.

Min. Bend Radius/Minor Axis: 3.250 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

## 4794R Coax - 4K Ultra-High-Definition Coax Cable for 12G-SDI

MII Order #39 (China RoHS):	Yes
Series Type:	Series 7

### Flame Test

UL Flame Test:	UL1666 Vertical Shaft
CSA Flame Test:	FT4

### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes - Black only.
Suitability - Aerial:	Yes - Black only, when supported by messenger wire.
Suitability - Burial:	No

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Electrical Characteristics (Overall)

#### Nom. Characteristic Impedance:

Impedance (Ohm)
75

#### Nom. Inductance:

Inductance (µH/ft)
0.091

#### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
15.500

#### Nominal Velocity of Propagation:

VP (%)
85.000

#### Nominal Delay:

Delay (ns/ft)
1.200

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
4.000

#### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
1.900

#### Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.260
3.580	0.430
5.000	0.500
6.000	0.520
7.000	0.550
10.000	0.630
12.000	0.660
25.000	0.880
55.000	1.210
67.500	1.310
71.500	1.340
88.500	1.470
100.000	1.540
135.000	1.750
143.000	1.790
180.000	1.980
270.000	2.400
360.000	2.760
540.000	3.410
720.000	3.960
750.000	4.050
1000.000	4.700
1500.000	5.830
2000.000	6.800

## 4794R Coax - 4K Ultra-High-Definition Coax Cable for 12G-SDI

2250.000	7.250
3000.000	8.480
4500.000	10.660
6000.000	12.470
12000.000	19.450

**Max. Operating Voltage - UL:**

<b>Voltage</b>
300 V RMS

**Other Electrical Characteristic 1:**

Return Loss: Fixed bridge and termination.

**Minimum Return Loss:**

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5.000	1600.000	23.000
1600.000	4500.000	21.000
4500.000	12000.000	15.000

**Sweep Test**

**Sweep Testing:**

Sweep tested 5 MHz to 12 GHz.

**Notes (Overall)**

**Notes:** Print legend includes sequential footage marks.

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
4794R N3U1000	1,000 FT	60.000 LB	GREEN, MIL		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0021000	1,000 FT	60.000 LB	RED		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0031000	1,000 FT	60.000 LB	ORANGE		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0041000	1,000 FT	60.000 LB	YELLOW		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0061000	1,000 FT	60.000 LB	BLUE, LIGHT		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0071000	1,000 FT	60.000 LB	VIOLET		#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0101000	1,000 FT	60.000 LB	BLACK	C	#16 LDPE/GIFHDLDPPE SH FRPVC
4794R 0102500	2,500 FT	145.000 LB	BLACK	C Z	#16 LDPE/GIFHDLDPPE SH FRPVC

**Notes:**

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 4    Revision Date: 04-12-2017

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).