

Part Number: 1313A

Speaker Cable, 2 Conductor 10 AWG BC, Unshielded, CM



Product Description

Speaker Cable, 2 Conductor 10 AWG stranded high conductivity bare copper conductors with polyolefin insulation, CL3 & CM-Rated, PVC jacket.

Technical Specifications

Product Overview

Environmental Space:	Indoor (Not Riser or Plenum)
Suitable Applications:	Speaker Cable, Direct Burial, Indoor/Outdoor Home Theater, In-Wall Speaker, Outdoor Speaker

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors
10	259x34	High Conductivity BC - Bare Copper	0.132 in	2

Conductor Count:	2
Conductor Size:	10 AWG

Insulation

Material	Nominal Diameter
PO - Polyolefin	0.17 in

Color Chart

Number	Color
1	Black
2	Red

Outer Shield Material

Material
Unshielded

Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.428 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
1 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	
23.2 pF/ft	
Shielding:	Unshielded

Inductance

Nominal Inductance
0.15 μ H/ft

Delay

Nominal Velocity of Propagation (VP) [%]

66 %

Current**Max. Recommended Current [A]**

17 Amps per conductor @ 25°C

Voltage**UL Voltage Rating**

300V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	100 lbs/1000ft
Max Recommended Pulling Tension:	275 lbs
Min Bend Radius/Minor Axis:	4.5 in

Standards

NEC/(UL) Specification:	CL3, CM
CEC/C(UL) Specification:	CM
CPR Euroclass:	Eca
Other Specification:	Sunlight resistant in Black and White.

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-11
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1581 Vertical Flame and FT-1 Flame Test
CSA Flammability:	FT1
UL Voltage Rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6T00UP

Part Number**Variants**

Item #	Color	Footnote
1313A 0101000	BLACK	C
1313A 010500	BLACK	C
1313A 0081000	GRAY	C
1313A 008500	GRAY	C
1313A 1SL1000	WHITE 1SL	C
1313A 1SL500	WHITE 1SL	C

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.