



**Part Number:** 1802B

Audio Cable, #24-2pr, TC, O/A Foil, CMG

## Product Description

Digital Audio Cable, CMG-Rated, 2-24 AWG stranded tinned copper pairs with Datalene® insulation, Beldfoil® shield, drain, PVC jacket, parallel construction

## Technical Specifications

### Product Overview

Environmental Space:	Indoor (Not Riser or Plenum)
----------------------	------------------------------

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
24	7x32	TC - Tinned Copper	0.024 in	2

Conductor Count:	4
Total Number of Pairs:	2
Conductor Size:	24 AWG

#### Insulation

Material	Material Trade Name	Nominal Diameter
FHDPE - Foamed High Density Polyethylene	Datalene®	0.68 in

#### Color Chart

Number	Color
1	Red & Black
2	Red & Black

#### Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Diameter	Drainwire AWG	Drainwire Construction n x D
Tape	Bonded Aluminum Foil-Polyester Tape (bonded to jacket)	Beldfoil®	100 %	0.024 in	24	7x32 mm
					TC - Tinned Copper	

#### Outer Shield Material

Material
Unshielded

#### Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	.180 x .360 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
23.7 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
12 pF/ft	26 pF/ft

Shielding:	Foil(s) or Copper Tape(s)
------------	---------------------------

#### Inductance

##### Nominal Inductance

0.18  $\mu$ H/ft

#### Impedance

##### Nominal Characteristic Impedance

110 Ohm

#### High Frequency (Nominal/Typical)

##### Nom. Insertion Loss

0.69 dB/100ft

0.93 dB/100ft

0.96 dB/100ft

1.07 dB/100ft

1.19 dB/100ft

1.21 dB/100ft

1.31 dB/100ft

1.41 dB/100ft

1.45 dB/100ft

1.57 dB/100ft

1.76 dB/100ft

1.83 dB/100ft

2.01 dB/100ft

2.24 dB/100ft

2.3 dB/100ft

3.08 dB/100ft

#### Delay

##### Nominal Velocity of Propagation (VP) [%]

76 %

#### High Freq

##### Frequency [MHz]

0.384 MHz

0.7056 MHz

0.768 MHz

1.024 MHz

1.4112 MHz

1.536 MHz

2.048 MHz

2.8224 MHz

3.072 MHz

4.096 MHz

5.6448 MHz

6.144 MHz

8.192 MHz

11.2896 MHz

12.288 MHz

24.576 MHz

#### Current

##### Max. Recommended Current [A]

2.75 Amps per conductor @ 25°C

#### Voltage

##### UL Voltage Rating

300V RMS

#### Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-30°C To +60°C

## Mechanical Characteristics

UV Resistance:	No
Bulk Cable Weight:	33 lbs/1000ft
Max Recommended Pulling Tension:	33 lbs
Min Bend Radius/Minor Axis:	2 in

## Standards

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMR
Other Specification:	AES/EBU

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

## Flammability, LS0H, Toxicity Testing

CSA Flammability:	FT4
UL Voltage Rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	Footnote
1802B 010N1000	BLACK	
1802B Z4B1000	VIOLET Z4B	C
1802B Z4B500	VIOLET Z4B	C
1802B Z4BU1000	VIOLET Z4B	
1802B Z4BN1000	VIO Z4B	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.