



Part Number: 83396

Control/Instrumentation, (4) 22 AWG (7x30) TC, FEP/Silicone rubber, Foil+Nylon Shld

## **Product Description**

Four 22 AWG stranded (7x30) TC conductors, Teflon® (FEP) insulation, noise reducing tape, overall Beldfoil® shield (100% coverage), silicone rubber jacket.

# **Technical Specifications**

#### **Physical Characteristics (Overall)**

# Conductors AWG Stranding Material No. of Conductors 22 7x30 TC - Tinned Copper 4 Conductor Count: 4 Conductor Size: 22 AWG

#### Insulation

Material	Material Trade Name	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	Teflon®	0.0155 in

### Color Chart

Number	Color
1	Black
2	White
3	Red
4	Green

#### **Outer Shield Material**

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	22	7x30 mm
Таре	2	Noise Reducing Conductive Nylon					

## **Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness
Silicone Rubber	0.217 in	0.03 in

# **Electrical Characteristics**

# Conductor DCR



# Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Sh
22 pF/ft	40 pF/ft
Shielding:	Foil(s) or Cop

#### Current



Voltage

Non-UL Description	Non-UL Voltage Rating	Voltage Rating [V]
Between Conductors	350 V RMS Between Conductors	2000V DC Through Jacket
Through Jacket	2000 V DC V	

#### **Temperature Range**

O	perating Temp Range:	-70°C To +150°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	32 lbs/1000ft
Max Recommended Pulling Tension:	40 lbs
Min Bend Radius/Minor Axis:	2.25 in

#### **Standards**

UL AWM Style:	UL Style 4516 (600 V 150°C)
CPR Euroclass:	Eca
Other Specification:	NEMA HP3

#### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Plenum/Non-Plenum

Plenum (Y/N):	No	

## **Part Number**

## Variants

varianto		
Item #	Color	Footnote
83396 002100	RED	
83396 002500	RED	С
Footnote:		

#### © 2018 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.