


Part Number: 8450

Audio & Instrumentation, #22-1pr, TC, O/A Foil, CM



Product Description

22 AWG solid tinned copper conductors, polypropylene insulation, twisted pair, overall Beldfoil® shield (100% coverage), 22 AWG solid TC drain wire, PVC jacket.

Technical Specifications

Product Overview

Environmental Space:	Indoor (Not Riser or Plenum)
----------------------	------------------------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	Solid	TC - Tinned Copper	0.02635 in	1

Conductor Count:	2
Total Number of Pairs:	1
Conductor Size:	22 AWG

Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.007 in

Color Chart

Number	Color
1	Black & Red

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire Diameter	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil® (Z-Fold®)	100 %	TC - Tinned Copper	0.02635 mm	22	Solid

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.118 in	0.018 in
	0.118 in	

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR	Conductor Resistance	Nominal Outer Shield DCR
16.1 Ohm/1000ft	16.1 Ohm/1000ft		12.65 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
40 pF/ft	76 pF/ft

Shielding:	Foil(s) or Copper Tape(s)
------------	---------------------------

Inductance

Nominal Inductance
0.08 µH/ft

Impedance

Nominal Characteristic Impedance

40 Ohm

Delay

Nominal Delay

1.5 ns/ft

Nominal Velocity of Propagation (VP) [%]

66 %

Current

Max. Recommended Current [A]

2.9 Amps per conductor @ 25°C

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

UL Temp Rating:

75°C

Operating Temp Range:

-20°C To +105°C

Mechanical Characteristics

Bulk Cable Weight:

12 lbs/1000ft

Max Recommended Pulling Tension:

37 lbs

Min Bend Radius/Minor Axis:

1.25 in

Standards

NEC/(UL) Specification:

CM

CEC/C(UL) Specification:

CM

CPR Euroclass:

Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):

Yes

EU Directive 2003/11/EC (BFR):

Yes

EU Directive 2011/65/EU (ROHS II):

Yes

EU Directive 2012/19/EU (WEEE):

Yes

EU Directive 2015/863/EU:

Yes

EU Directive Compliance:

EU Directive 2003/11/EC (BFR)

EU CE Mark:

Yes

EU RoHS Compliance Date (yyyy-mm-dd):

2004-01-01

CA Prop 65 (CJ for Wire & Cable):

Yes

MII Order #39 (China RoHS):

Yes

Flammability, LSOH, Toxicity Testing

UL Flammability:

UL1685 UL Loading

UL Voltage Rating:

300V RMS

Plenum/Non-Plenum

Plenum (Y/N):

No

Part Number

Variants

Item #	Color
8450 0101000	BLACK
8450 010U1000	BLACK
8450 010U500	BLACK
8450 0081000	GRAY

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.