

**Part Number: 9452**

Microphone Cable, #24-1pr, TC, O/A Foil, CM



## Product Description

24 AWG stranded (19x36) HC TC conductors, high-density polyethylene insulation, twisted pair, noise reducing tape, Beldfoil® shield (100% coverage), 24 AWG stranded TC drain wire, PVC jacket.

## Technical Specifications

### Product Overview

Environmental Space:	Indoor (Not Riser or Plenum)
----------------------	------------------------------

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors
24	19x36	High Conductivity TC - Tinned Copper	0.024 in	2

Conductor Count:	2
Conductor Size:	24 AWG

#### Insulation

Material	Nominal Diameter	Nominal Wall Thickness
HDPE - High Density Polyethylene	0.04 in	0.008 in

#### Color Chart

Color
Black
Red

#### Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire Diameter	Drainwire AWG	Drainwire Construction n x D
Tape	1	Noise Reducing		100 %	TC - Tinned Copper	0.025 in	24	Stranded
Tape	2	Aluminum Foil-Polyester Tape	Beldfoil®	100 %				

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.135 in	0.020 in
	0.135 in	

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR	Conductor Resistance	Nominal Outer Shield DCR
25 Ohm/1000ft	25 Ohm/1000ft		16.5 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
30 pF/ft	58 pF/ft

Shielding:	Foil(s) or Copper Tape(s)
------------	---------------------------

#### Inductance

Nominal Inductance
--------------------

0.18 µH/ft

#### Impedance

##### Nominal Characteristic Impedance

56 Ohm

#### Current

##### Max. Recommended Current [A]

2.2 Amps per conductor @ 25°C

#### Voltage

##### Non-UL Voltage Rating

200 V RMS

#### Temperature Range

Non-UL Temp Rating:	75°C
Operating Temp Range:	-40°C To +75°C

#### Mechanical Characteristics

Bulk Cable Weight:	11 lbs/1000ft
Max Recommended Pulling Tension:	17.7 lbs
Min Bend Radius/Minor Axis:	1.5 in

#### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

#### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

#### Part Number

#### Variants

Item #	Color
9452 0101000	BLACK
9452 010500	BLACK
9452 010U1000	BLACK
9452 010U500	BLACK

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.