

Part Number: 6341PC



Security & Sound, 2 Pair 18 AWG, BC, Individually Shielded, CMP

Product Description

Security, Pro Audio & Intercom Cable, Plenum-CMP, 2-18 AWG stranded bare copper pairs with FEP insulation, Individually Beldfoil® shielded and Flamarrest® jacket

Technical Specifications

Product Overview

| Physical Characteristics (Overall) Conductor AWG Stranding Material No. of Pairs 18 7 BC - Bare Copper 2 Conductor Count: 3 Total Number of Pairs: 2 Conductor Size: 18 AWG | Enviro | nmental Spa | ice: | | | | Indoor - P |
|---|------------------------|-------------------------------------|------------------|--------|--|--|------------|
| AWG Stranding Material No. of Pairs 18 7 BC - Bare Copper 2 Conductor Count: 3 Total Number of Pairs: 2 | Phys | Physical Characteristics (Overall) | | | | | |
| 18 7 BC - Bare Copper 2 Conductor Count: 3 Total Number of Pairs: 2 | Condu | ctor | | | | | |
| Conductor Count: 3 Total Number of Pairs: 2 | AWG | AWG Stranding Material No. of Pairs | | | | | |
| Total Number of Pairs: 2 | 18 | 7 | BC - Bare Copper | 2 | | | |
| | Conductor Count: | | | 3 | | | |
| Conductor Size: 18 AWG | Total Number of Pairs: | | 2 | | | | |
| | Conductor Size: | | | 18 AWG | | | |

Insulation

| Material | Nominal Wall Thickness | |
|--------------------------------------|------------------------|--|
| FEP - Fluorinated Ethylene Propylene | 0.01 in | |

Color Chart

| Number | Color |
|--------|-----------------|
| 1 | Black and Red |
| 2 | Black and White |

Inner Shield Material

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|------------------------------|---------------------|--------------|--------------------|--------------------|------------------------------|
| Таре | Aluminum Foil-Polyester Tape | Beldfoil® | 100 % | Tinned Copper | 24 | 7 mm |
| | | | | | TC - Tinned Copper | |

Outer Shield Material



Outer Jacket Material

| Material | Material Trade Name | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|---------------------------------------|---------------------|------------------|------------------------|---------|
| LS PVC - Low Smoke Polyvinyl Chloride | Flamarrest® | 0.281 in | 0.0165 in | Yes |

Construction and Dimensions

Stranding



Electrical Characteristics

| Individual Pair Nominal Shield DCR | Nominal Conductor DCR | Nominal Inner Shield DCR |
|------------------------------------|-----------------------|--------------------------|
| 14.4 Ohm/1000ft | 6.5 Ohm/1000ft | 14.4 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conduc | ctor to Shield |
|---|--|---------------------|
| 44 pF/ft | 79.2 pF/ft | |
| Shielding: | Individua | ally Foiled + No Ov |

Inductance

Individually Foiled + No Overall

0.16 µH/ft

Current

Max. Recommended Current [A] 4 Amps per conductor @ 25°C

Voltage

UL Voltage Rating 300V RMS

Temperature Range

| Ī | UL Temp Rating: | 75°C | |
|---|-----------------|------|---|
| | UL Temp Rating: | /5°C | l |

Mechanical Characteristics

| Bulk Cable Weight: | 43.3 lbs/1000ft | |
|----------------------------------|-----------------|--|
| Max Recommended Pulling Tension: | 117.6 lbs | |
| Min Bend Radius/Minor Axis: | 2.75 in | |

Standards

| NEC/(UL) Specification: | CMP |
|--------------------------|-----|
| CEC/C(UL) Specification: | CMP |

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| C(UL) Flammability: | FT6 |
|---------------------|-----------|
| UL Flammability: | NFPA 262 |
| UL Voltage Rating: | 300 V RMS |

Plenum/Non-Plenum

Part Number

Variants

| | Item # | Color | Footnote |
|---|-----------------|---------|----------|
| ľ | 6341PC 8771000 | NATURAL | С |
| ľ | 6341PC 877500 | NATURAL | |
| ľ | 6341PC 877U1000 | NATURAL | |

Footnote: C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.