

Part Number: 87777

Audio, Control & Instrument, #22-3pr, FEP, Individ. Foil, PVDF Jkt, CMP



Product Description

Audio, Control & Instrument Cable, 22 AWG stranded (7x30) tinned copper conductor, FEP insulation, twisted pairs individually shielded with Beldfoil® (100% coverage), overall jacket per table below, 22 AWG stranded tinned copper drain wire.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	7x30	TC - Tinned Copper	0.03 in	3

Conductor Count:	6
Conductor Size:	22 AWG

Insulation

Material	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.01 in

Color Chart

Number	Color
1	Black & Red
2	Black & White
3	Black & Green

Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil® (Z-Fold®)	100 %	TC - Tinned Copper	22	Stranded mm

Outer Shield Material

Material	Drainwire AWG
Unshielded	22

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVDF - Polyvinylidene Fluoride	0.234 in	0.014 in

Electrical Characteristics

Conductor DCR

Individual Pair Nominal Shield DCR	Max. Conductor DCR
11.3 Ohm/1000ft	16 Ohm/100m

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
31 pF/ft	67 pF/ft

Shielding:	Individually Foiled + No Overall
------------	----------------------------------

Inductance

Nominal Inductance

0.18 µH/ft

Impedance

Nominal Characteristic Impedance

50 Ohm

Delay

Max. Delay Skew | Nominal Delay | Nominal Velocity of Propagation (VP) [%]

69 ns/100m | 1.47 ns/ft | 69 %

Current

Max. Recommended Current [A]

3.5 Amps per conductor @ 25°C A

Voltage

UL Voltage Rating

300V RMS

Temperature Range

Operating Temp Range: -20°C To +150°C

Mechanical Characteristics

Bulk Cable Weight: 36 lbs/1000ft

Max Recommended Pulling Tension: 82 lbs

Min Bend Radius/Minor Axis: 2.5 in

Standards

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2005-04-01

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flammability, LSOH, Toxicity Testing

UL Flammability: NFPA 262 Plenum Flame Test (UL910)

CSA Flammability: FT6

Plenum/Non-Plenum

Plenum (Y/N): Yes

Part Number

Non-Plenum Number: 8777

Variants

Item #	Color	Footnote
87777 0021000	RED	C
87777 002500	RED	C

Footnote: C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.