

10GX53F Multi-Conductor - Enhanced Category 6A F/UTP Non-Bonded Pair Cable



For more Information
please call

1-800-Belden1



General Description:

CAT6A (625MHz), 4-Non-Bonded Pair, F/UTP-Foil Shielded, Plenum-CMP, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, FEP Insulation, Patented X-Spline, Inner Jacket, Overall Foil Screen with Drain Wire, Ripcord, Flamarrest® Jacket

Usage (Overall)

Suitable Applications: Premise Horizontal Cable, 10 Gigabit Ethernet, 100Base TX, 100Base VG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio AES51, RS-422, Noisy Environments, PoE, PoE+

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4 | 23 | Solid | BC - Bare Copper |

Total Number of Conductors: 8

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| FEP |

Outer Shield

Outer Shield Material:

| Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|-------------------------|------|-------------------------|--------------|
| Beldfoil® | Tape | Aluminum-Polyester Tape | 100.000 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire | Conductor Material |
|-----|-----------|---------------|--------------------|
| 26 | 7x#34 | Tinned Copper | |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|---|
| Flamarrest (R) PVC - Polyvinyl Chloride |

Outer Jacket Diameter:

| Nom. Dia. (in.) |
|-----------------|
| 0.275 |

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Separator Material: Patented EquiSpline

Pair

Pair Color Code Chart:

| Number | Color |
|--------|----------------|
| 1 | Blue & White |
| 2 | Orange & White |
| 3 | Green & White |
| 4 | Brown & White |

Mechanical Characteristics (Overall)

Storage Temperature Range: -20°C To +80°C

Installation Temperature Range: -5°C To + 50°

Operating Temperature Range: -10°C To +90°C

Bulk Cable Weight: 42 lbs/1000 ft.

Max. Recommended Pulling Tension: 45 lbs.

10GX53F Multi-Conductor - Enhanced Category 6A F/UTP Non-Bonded Pair Cable

| | |
|------------------------------|-----------|
| Min. Bend Radius/Minor Axis: | 1.500 in. |
| Min. Bend/Installation: | 2.750 in. |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|--|
| NEC/(UL) Specification: | CMP |
| CEC/C(UL) Specification: | CMP |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| Other Standards: | ISO/IEC 11801 ed 2 Amendment 2:2010 Class EA |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 03/27/2014 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Telecommunications Standards: | Category 6A - TIA 568.C.2 |
| ANSI Specification: | ANSI/TIA 568-C.2 Category 6A |

Applicable Patents:

| |
|------------------|
| Country |
| www.belden.com/p |

Flame Test

| | |
|-------------------|---|
| UL Flame Test: | NFPA 262 Plenum Flame Test (UL910)(FT6) |
| C(UL) Flame Test: | FT6 |
| CSA Flame Test: | FT6 |

Suitability

| | |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | No |
| Suitability - Burial: | No |
| Sunlight Resistance: | No |
| Non-halogenated: | No |

Plenum/Non-Plenum

| | |
|--------------------|---------|
| Plenum (Y/N): | Yes |
| Non-Plenum Number: | 10GX52F |

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

| |
|---------------------|
| Capacitance (pF/ft) |
| 17.000 |

| | |
|---|----|
| Maximum Capacitance Unbalance (pF/100 m): | 90 |
|---|----|

Nominal Velocity of Propagation:

| |
|--------|
| VP (%) |
| 68.000 |

Maximum Delay:

| |
|------------------|
| Delay (ns/100 m) |
| 538 @ 100MHz |

Max. Delay Skew:

| |
|-----------------------|
| Delay Skew (ns/100 m) |
| 45.000 |

Maximum Conductor DC Resistance:

| |
|------------------------|
| DCR @ 20°C (Ohm/100 m) |
| 8.200 |

Max. Operating Voltage - UL:

| |
|---------|
| Voltage |
|---------|

10GX53F Multi-Conductor - Enhanced Category 6A F/UTP Non-Bonded Pair Cable

300 V RMS

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. PSNEXT (dB) | Min. PSACR (dB) | Min RL (dB) |
|-------------|-----------------------------|------------------|-----------------|-------------|
| 1 | 2.100 | 73.3 | 71.2 | 20.000 |
| 4 | 3.800 | 64.3 | 60.5 | 23.000 |
| 8 | 5.300 | 59.8 | 54.4 | 24.500 |
| 10 | 5.900 | 58.3 | 52.4 | 25.000 |
| 16 | 7.500 | 55.2 | 47.8 | 25.000 |
| 20 | 8.400 | 53.8 | 45.4 | 25.000 |
| 25 | 9.400 | 52.3 | 43.0 | 24.300 |
| 31.25 | 10.500 | 50.9 | 40.4 | 23.600 |
| 62.5 | 15.000 | 46.4 | 31.4 | 21.500 |
| 100 | 19.100 | 43.3 | 24.2 | 20.100 |
| 200 | 27.600 | 38.8 | 11.2 | 18.000 |
| 250 | 31.100 | 37.3 | 6.3 | 17.300 |
| 300 | 34.300 | 36.1 | 1.9 | 16.800 |
| 350 | 37.200 | 35.1 | N/A | 16.300 |
| 400 | 40.100 | 34.3 | N/A | 15.900 |
| 450 | 42.700 | 33.5 | N/A | 15.500 |
| 500 | 45.300 | 32.8 | N/A | 15.200 |
| 550 | 47.700 | 32.2 | N/A | 14.900 |
| 600 | 50.100 | 31.6 | N/A | 14.700 |
| 625 | 51.200 | 31.4 | N/A | 14.500 |
| 750 | 56.700 | 30.2 | N/A | 14.000 |
| 860 | 61.200 | 29.3 | N/A | 13.600 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. PSACRF (dB) |
|-------------|------------------------------|------------------|------------------|
| 1 | 100 ± 15 | 105 ± 10 | 68.8 |
| 4 | 100 ± 15 | 100 ± 15 | 56.8 |
| 8 | 100 ± 15 | 100 ± 15 | 50.7 |
| 10 | 100 ± 15 | 100 ± 15 | 48.8 |
| 16 | 100 ± 15 | 100 ± 15 | 44.7 |
| 20 | 100 ± 15 | 100 ± 15 | 42.8 |
| 25 | 100 ± 15 | 100 ± 15 | 40.8 |
| 31.25 | 100 ± 15 | 100 ± 10 | 38.9 |
| 62.5 | 100 ± 15 | 100 ± 10 | 32.9 |
| 100 | 100 ± 15 | 100 ± 10 | 28.8 |
| 200 | 100 ± 22 | 100 ± 10 | 22.8 |
| 250 | 100 ± 32 | 100 ± 10 | 20.8 |
| 300 | 100 ± 32 | 100 ± 10 | 19.3 |
| 350 | 100 ± 32 | 100 ± 10 | 17.9 |
| 400 | 100 ± 32 | 100 ± 10 | 16.8 |
| 450 | 100 ± 32 | 100 ± 10 | 15.7 |
| 500 | 100 ± 32 | 100 ± 10 | 14.8 |
| 550 | 100 ± 32 | 100 ± 10 | 14.0 |
| 600 | 100 ± 32 | 100 ± 10 | 13.2 |
| 625 | 100 ± 32 | 100 ± 10 | 12.9 |
| 750 | 100 ± 32 | 100 ± 10 | 11.3 |
| 860 | 100 ± 32 | 100 ± 10 | 10.1 |

Premise Cable Electrical Table 4:

| Frequency (MHz) | Min. PSANEXT (dB) | Min. PSAACRF (dB) | Min. TCL (dB) | Min. ELTCTL (dB) |
|-----------------|-------------------|-------------------|---------------|------------------|
| 1.000 | 77.000 | 77.000 | 40.000 | 35.000 |
| 4.000 | 77.000 | 76.200 | 40.000 | 23.000 |
| 8.000 | 77.000 | 70.100 | 40.000 | 16.900 |
| 10.000 | 77.000 | 68.200 | 40.000 | 15.000 |
| 16.000 | 77.000 | 64.100 | 38.000 | 10.900 |
| 20.000 | 77.000 | 62.200 | 37.000 | 9.000 |
| 25.000 | 77.000 | 60.200 | 36.000 | 7.000 |
| 31.250 | 77.000 | 58.300 | 35.100 | |
| 62.500 | 77.000 | 52.300 | 32.000 | |
| 100.000 | 72.500 | 48.200 | 30.000 | |
| 200.000 | 68.500 | 42.200 | 27.000 | |
| 250.000 | 66.500 | 40.200 | 26.000 | |
| 300.000 | 65.300 | 38.700 | 25.300 | |

ENGLISH MEASUREMENT VERSION

10GX53F Multi-Conductor - Enhanced Category 6A F/UTP Non-Bonded Pair Cable

| | | | | |
|---------|--------|--------|--------|--|
| 350.000 | 64.300 | 37.300 | 24.600 | |
| 400.000 | 63.500 | 36.200 | 24.000 | |
| 450.000 | 62.700 | 35.100 | 23.500 | |
| 500.000 | 62.000 | 34.200 | 23.000 | |
| 550.000 | 62.400 | 34.400 | | |
| 600.000 | 61.800 | 33.600 | | |
| 625.000 | 61.600 | 33.300 | | |
| 750.000 | 60.400 | 31.700 | | |
| 860.000 | 59.500 | 30.500 | | |

Notes (Overall)

Notes: Jacket sequentially marked at 2 ft. intervals. Third party channel verified to TIA/EIA-568-C.2, Category 6A. Data above 625 MHz For Information Only.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|-----------------|----------|-------------|--------|-------|--------------------------|
| 10GX53F D151000 | 1,000 FT | 41.000 LB | BLUE | | CAT6A 4PR F/UTP CMP REEL |
| 10GX53F 0041000 | 1,000 FT | 41.000 LB | YELLOW | | CAT6A 4PR F/UTP CMP REEL |
| 10GX53F 0081000 | 1,000 FT | 41.000 LB | GRAY | | CAT6A 4PR F/UTP CMP REEL |
| 10GX53F 0091000 | 1,000 FT | 41.000 LB | WHITE | | CAT6A 4PR F/UTP CMP REEL |
| 10GX53F 0101000 | 1,000 FT | 41.000 LB | BLACK | | CAT6A 4PR F/UTP CMP REEL |

Revision Number: 2 Revision Date: 03-03-2017

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).