


AX104215 Modular Connectors - CAT6+ KeyConnect RJ45 Coupler



For more Information
please call

1-800-Belden1



General Description:

CAT6+ KeyConnect RJ45 Coupler, Black

Usage (Overall)

| | |
|------------------------|-----------------------------------|
| Suitable Applications: | IBDN System CAT6+, TIA Category 6 |
| Related Parts: | CAT6+ Coupler Patch Panels |

Multi Conductor

Physical Characteristics
Overall Cabling
Overall Diameter

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

| Height (in.) | Width (in.) | Depth (in.) |
|--------------|-------------|-------------|
| 0.895 | 0.692 | 1.522 |

Materials

Materials:

| Description | Type | Material |
|------------------|--------------|---|
| Front Connection | Flexible PCB | Flexible PCB with 50u inch Gold over Nickel |
| Rear Connection | Flexible PCB | Flexible PCB with 50u inch Gold over Nickel |
| Connector Body | N/A | Plastic - UL94V-0 |

Color

| | |
|--------|-------|
| Color: | Black |
|--------|-------|

Wiring Scheme

| | |
|----------------|-----------------|
| Wiring Scheme: | T568A/B-T568A/B |
|----------------|-----------------|

Weight

| | |
|---------|------------|
| Weight: | 0.380 lbs. |
|---------|------------|

Packaging

| | |
|------------|---|
| Packaging: | Individually packaged in a clear plastic bag. |
|------------|---|

Mechanical Characteristics (Connectivity)

| | |
|-----------------|------------|
| Footprint/Type: | KeyConnect |
|-----------------|------------|

| | |
|----------------------------|------|
| Plug / Jack Compatibility: | RJ45 |
|----------------------------|------|

Termination Interface:

| Termination | Connection | Durabilities |
|-------------|------------------|--------------|
| Front | Mated Connection | 750 cycles |
| Rear | Mated Connection | 750 cycles |

| | |
|-------------------------------|---------|
| Connector/Hardware Retention: | 20 lbs. |
|-------------------------------|---------|

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|---|
| Other Standards: | FCC Part 68, Subpart F, IEC 60603-7 |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 08/01/2009 |
| MII Order #39 (China RoHS): | EUP 50 |
| Telecommunications Standards: | Category 6 - TIA 568.C.2, ISO/IEC 11801:2002 Ed.2 |
| Safety Listing: | Bi-national Standard Listed |

Suitability

| | |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

AX104215 Modular Connectors - CAT6+ KeyConnect RJ45 Coupler

Plenum/Non-Plenum

Transmission Characteristics (Connectivity)

Mated Connection Table 1:

| Frequency (MHz) | Max. Insertion Loss TIA* (dB) | Max. Insertion Loss Belden** (dB) | Min. NEXT TIA* (dB) | Min. NEXT Belden** (dB) | Min. FEXT TIA* (dB) | Min. FEXT Belden** (dB) |
|-----------------|-------------------------------|-----------------------------------|---------------------|-------------------------|---------------------|-------------------------|
| 1.000 | 0.100 | 0.100 | 75.000 | 75.000 | 75.000 | 77.000 |
| 4.000 | 0.100 | 0.100 | 75.000 | 75.000 | 71.100 | 75.100 |
| 8.000 | 0.100 | 0.100 | 75.000 | 75.000 | 65.000 | 69.000 |
| 10.000 | 0.100 | 0.100 | 74.000 | 74.000 | 63.100 | 67.100 |
| 16.000 | 0.100 | 0.100 | 69.900 | 69.900 | 59.000 | 63.000 |
| 20.000 | 0.100 | 0.100 | 68.000 | 68.000 | 57.100 | 61.100 |
| 25.000 | 0.100 | 0.100 | 66.000 | 66.000 | 55.100 | 59.100 |
| 31.250 | 0.110 | 0.110 | 64.100 | 64.100 | 53.200 | 57.200 |
| 62.500 | 0.160 | 0.160 | 58.100 | 58.100 | 47.200 | 51.200 |
| 100.000 | 0.200 | 0.200 | 54.000 | 54.000 | 43.100 | 47.100 |
| 200.000 | 0.280 | 0.280 | 48.000 | 48.000 | 37.100 | 41.100 |
| 250.000 | 0.320 | 0.320 | 46.000 | 46.000 | 35.100 | 39.100 |
| 280.000 | | 0.330 | | 44.100 | | 38.200 |
| 300.000 | | 0.350 | | 42.900 | | 37.600 |

Mated Connection Table - Footnote:

* TIA/EIA-568-C.2 Category 6 Standard. ** Worst-case performance for a CAT6+ mated connection using CAT6+ modular plugs on both sides

Mated Connection Table 2:

| Frequency (MHz) | Min. Return Loss TIA* (dB) | Min. Return Loss Belden** (dB) | Min. Balanced TCL/TCTL TIA* (dB) | Min. Balanced TCL/TCTL Belden** (dB) |
|-----------------|----------------------------|--------------------------------|----------------------------------|--------------------------------------|
| 1.000 | 30.000 | 32.000 | 40.000 | 42.000 |
| 4.000 | 30.000 | 32.000 | 40.000 | 42.000 |
| 8.000 | 30.000 | 32.000 | 40.000 | 42.000 |
| 10.000 | 30.000 | 32.000 | 40.000 | 42.000 |
| 16.000 | 30.000 | 32.000 | 40.000 | 42.000 |
| 20.000 | 30.000 | 32.000 | 40.000 | 42.000 |
| 25.000 | 30.000 | 32.000 | 40.000 | 42.000 |
| 31.250 | 30.000 | 32.000 | 38.100 | 42.000 |
| 62.500 | 28.100 | 32.000 | 32.100 | 36.100 |
| 100.000 | 24.000 | 28.000 | 28.000 | 32.000 |
| 200.000 | 18.000 | 22.000 | 22.000 | 26.000 |
| 250.000 | 16.000 | 20.000 | 20.000 | 24.000 |
| 280.000 | | 19.100 | | 23.100 |
| 300.000 | | 18.500 | | 22.500 |

Dielectric Strength: 1,000 V RMS @ 60 Hz for 1 minute

Current Rating: 1.500 A

Insulation Resistance: 500 M-Ohm Minimum

Max. Contact Resistance: 20 m-Ohm

Notes (Overall)

Product Family

Part Number List:

| Item Number | Color |
|-------------|--------|
| AX104206 | Orange |
| AX104207 | Red |
| AX104208 | Yellow |
| AX104209 | Green |
| AX104210 | Blue |
| AX104213 | Gray |
| AX104214 | White |
| AX104215 | Black |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------|-------|-------------|-------|-------|-----------------------------|
| AX104215 | 1 EA | 0.033 LB | | | CAT6+ KCONN RJ45 COUPLER,BK |

AX104215 Modular Connectors - CAT6+ KeyConnect RJ45 Coupler

Revision Number: 0 Revision Date: 04-16-2013

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.