



Product Description

Two 12 AWG stranded (7x20) bare copper conductors, PVC/Nylon insulation, PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No.	of Conductors
12	7x20	BC - Bare Copper	2	
Condu	ctor Count:			2
AWG Size:			12	

Insulation

Material	Nominal Diameter	
PVC/Nylon - Polyvinyl Chloride/Nylon	0.134 in	

Color Chart

Number	Color
1	Black
2	Red

Outer Shield Material

Material Unshielded

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.234 x 0.372 in	0.048 in

Construction and Dimensions

Stranding

Lay Length N mm

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 1.65 Ohm/1000ft

Current

Max. Recommended Current [A] 30 Amps per conductor @ 25°C

Voltage

UL Voltage Rating
600 V RMS
150 V RMS

Temperature Range

UL Temp Rating:	75°C Dry, 90°C Wet
Wet Temp Range:	-30°C To +75 °C
Dry Temp Range:	-30°C To +90 °C

Mechanical Characteristics

Bulk Cable Weight:	83 lbs/1000ft
Max Recommended Pulling Tension:	122 lbs
Min Bend Radius/Minor Axis:	3.75 in

Standards

NEC/(UL) Specification:	TC, THHN, THWN, NPLF
Other Specification:	ICEA S-73-532, S-95-658, S-61-402

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU Directive Compliance: EU CE Mark:	EU Directive 2003/11/EC (BFR) Yes
	. ,
EU CE Mark:	Yes
EU CE Mark: EU RoHS Compliance Date (yyyy-mm-dd):	Yes 2005-04-01

Suitability

Suitability - Burial:	Yes
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT4
IEEE Flammability:	1202

Part Number

Plenum (Y/N):			No	
Variants				
Item #	Color	Footnote		

Footnote:			C - CRATE REEL PUT-UP.
27109A 0105000	BLACK		
27109A 01010000	BLACK	С	

Product Notes

|--|

Flat construction

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tiself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.