



Part Number: 7502A

MachFlex™ 75 Ohm Coax Vision, (1) 22 AWG (19x34) BC, FPE/PVC, TC Braid Shld

Product Description

One 22 AWG stranded (19x34) bare copper coax, foam polyethylene (FPE) insulation, tinned copper "French Style" braid shield (95% coverage), Belflex® PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
22	19x34	BC - Bare Copper	0.031 in	1

Conductor Count:	1
Conductor Size:	22 AWG

Insulation

Material	Nominal Diameter
FPE - Foamed Polyethylene	0.146 in

Outer Shield Material

Type	Material	Coverage [%]
French Braid	TC - Tinned Copper	95 %

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter
PVC - Polyvinyl Chloride	Belflex®	0.242 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
13.4 Ohm/1000ft	6.4 Ohm/1000ft	6.4 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield
18 pF/ft

Shielding:	Braid(s)
------------	----------

Inductance

Nominal Inductance
0.097 µH/ft

Impedance

Nominal Characteristic Impedance
75 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
2.2 MHz	0.4 dB/100ft
5 MHz	0.5 dB/100ft
10 MHz	0.8 dB/100ft

30 MHz	1.4 dB/100ft
50 MHz	1.8 dB/100ft
100 MHz	2.7 dB/100ft

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.3 ns/ft	79 %

High Freq

Frequency [MHz]
2.2 MHz
5 MHz
10 MHz
30 MHz
50 MHz
100 MHz

Voltage

UL Voltage Rating
30 V RMS

Temperature Range

Non-UL Temp Rating:	80°C
Operating Temp Range:	-40°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	30 lbs/1000ft
Max Recommended Pulling Tension:	38 lbs
Min Bend Radius (Continuous Flexing):	5 in
Min Bend Radius/Minor Axis:	2.5 in

Standards

UL AWM Style:	1354
CSA AWM Specification:	AWM I/II A/B

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT1
UL Voltage Rating:	30V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
7502A G7X1000	BLUE, MATTE	C Z
7502A G7X250	BLUE, MATTE	C Z
7502A G7X500	BLUE, MATTE	C Z

Footnote: C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.