



Part Number: 83350E

MIL-W-16878/4 (Type E), (4) 20 AWG (19x32) SPC, TFE/TFE, SPC Braid Shld

Product Description

Four 20 AWG stranded (19x32) silver-plated copper conductors, Teflon® (TFE) insulation, silver plated copper braid shield (85% coverage), Teflon® (TFE) jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
20	19x32	SPC - Silver Plated Copper	4

Conductor Count:	4
Conductor Size:	20 AWG

Insulation

Material	Material Trade Name	Nominal Wall Thickness
TFE - Tetrafluoroethylene	Teflon®	0.0105 in

Color Chart

Number	Color
1	White
2	Black
3	Red
4	Green

Outer Shield Material

Type	Material	Coverage [%]
Braid	SPC - Silver Plated Copper	85 %

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
TFE - Tetrafluoroethylene	Teflon®	0.183 in	0.011 in

Construction and Dimensions

Cabling

Lay Length
1.75 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
7.8 Ohm/1000ft	4.4 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
31.7 pF/ft	51 pF/ft
Shielding:	Braid(s)

Inductance

Nominal Inductance

0.145 µH/ft

Current

Max. Recommended Current [A]

6.5 Amps per conductor @ 25°C

Voltage

UL Voltage Rating

600V RMS

Temperature Range

Operating Temp Range: -65°C To +200°C

Mechanical Characteristics

Bulk Cable Weight: 35 lbs/1000ft

Max Recommended Pulling Tension: 94.7 lbs

Min Bend Radius/Minor Axis: 2 in

Standards

CPR Euroclass: Eca

Military Specification: MIL-W-16878/4 (Type E except stranding), (insulated conductors)

Other Specification: NEMA HP3

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU: Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2005-01-01

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flammability, LSOH, Toxicity Testing

UL Voltage Rating: 600 V RMS

Plenum/Non-Plenum

Plenum (Y/N): No

Part Number

Variants

Item #	Color	Footnote
83350E 009100	WHITE	E
83350E 0091000	WHITE	E
83350E 009500	WHITE	E

Footnote: E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

