



# **Product Description**

One 20 AWG pair stranded (19x32) tinned copper conductors, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

# **Technical Specifications**

## **Physical Characteristics (Overall)**

| Conductor               |                        |                    |              |
|-------------------------|------------------------|--------------------|--------------|
| AWG                     | Stranding              | Material           | No. of Pairs |
| 20                      | 19x32                  | TC - Tinned Copper | 1            |
| Conductor Count: 2      |                        | 2                  |              |
| Total I                 | Total Number of Pairs: |                    | 1            |
| Total Number of Triads: |                        | N/A                |              |
| AWG Size:               |                        | 20                 |              |

## Insulation

| Material                 | Nominal Wall Thickness |
|--------------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.0175 in              |

## Color Chart

NumberColor1Black & Red

## **Outer Shield Material**

| Туре | Material                     | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|------------------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Таре | Aluminum Foil-Polyester Tape | Beldfoil®           | 100 %        | TC - Tinned Copper | 22            | 19x34 mm                     |

## Outer Jacket Material

| Material                 | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | 0.221 in         | 0.037 in               | Yes     |

## **Electrical Characteristics**

| Conductor DCR |  |
|---------------|--|
|---------------|--|

| Nominal Conductor DCR | Nominal Outer Shield DCR |  |
|-----------------------|--------------------------|--|
| 9.5 Ohm/1000ft        | 17.75 Ohm/1000ft         |  |

### Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Shield |  |
|---|--------------------------------------|--|
| 52 pF/ft                                | 97 pF/ft                             |  |

## Inductance

Nominal Inductance 0.19 µH/ft

## Voltage

| UL Voltage Rating  |
|--------------------|
| 300V RMS (PLTC CMG |
| 150 V RMS (ITC)    |

## **Temperature Range**

| UL Temp Rating:       | 105°C           |
|-----------------------|-----------------|
| Operating Temp Range: | -30°C To +105°C |

#### **Mechanical Characteristics**

| Bulk Cable Weight:               | 26 lbs/1000ft |
|----------------------------------|---------------|
| Max Recommended Pulling Tension: | 16 lbs        |
| Min Bend Radius/Minor Axis:      | 2.16 in       |

## Standards

| NEC/(UL) Specification:  | CMG, ITC-ER, PLTC-ER       |
|--------------------------|----------------------------|
| CEC/C(UL) Specification: | CMG                        |
| UL AWM Style:            | UL Style 2464 (300 V 80°C) |

## Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV):        | Yes                           |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01                    |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                           |
| MII Order #39 (China RoHS):           | Yes                           |
|                                       |                               |

#### Suitability

| Suitability - Indoor:              | Yes |
|------------------------------------|-----|
| Suitability - Outdoor:             | Yes |
| Suitability - Sunlight Resistance: | Yes |

## Flammability, LS0H, Toxicity Testing

| C(UL) Flammability: | FT4                |
|---------------------|--------------------|
| UL Flammability:    | UL1685 FT4 Loading |
| IEEE Flammability:  | 1202               |

#### **Part Number**

| Plenum (Y/N): | No |  |  |
|---------------|----|--|--|

## Variants

| Item #        | Color  | Footnote |
|---------------|--------|----------|
| 9320 0605000  | CHROME | Z        |
| 9320 060U1000 | CHROME |          |
| 9320 060U500  | CHROME |          |
| Footnote:     |        |          |

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tiself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.