



Part Number: 9365

300V PLTC, (1 triad) 18 AWG (19x30) TC, PVC/PVC, Foil Shld, TC

## **Product Description**

One 18 AWG triad stranded (19x30) tinned copper conductors, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

## **Technical Specifications**

#### **Physical Characteristics (Overall)**

# Conductor Element AWG Stranding Material No. of Triads Triad 18 19x30 TC - Tinned Copper 1 Conductor Count: 3 Total Number of Pairs: N/A Total Number of Triads: 1 AWG Size: 18

#### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.017 in

#### Color Chart

Number	Color
1	Black & White & Red

#### **Outer Shield Material**

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	20	19x32 mm

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.260 in	0.037 in	Yes

### **Construction and Dimensions**

#### Cabling



## **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
5.86 Ohm/1000ft	9.5 Ohm/1000ft

## Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
54 pF/ft	101 pF/ft

#### Inductance

Nominal Inductance

#### Impedance

Nominal	Characteristic Impedance
45 Ohm	

# Voltage

<b>UL Description</b>	UL Voltage Rating
PLTC, CMG	300V RMS
ITC	150 V RMS

# **Temperature Range**

UL Temp Rating:	80°C
Operating Temp Range:	-30°C To +105°C

## **Mechanical Characteristics**

Bulk Cable Weight:	39 lbs/1000ft
Max Recommended Pulling Tension:	39 lbs
Min Bend Radius/Minor Axis:	2.5 in

## Standards

NEC/(UL) Specification:	CMG, ITC-ER, PLTC-ER
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2464 (300 V 80°C)

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EO Directive 2000/55/EC (ELV).	165
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## **Suitability**

Suitability - Burial:	Yes
Suitability - Sunlight Resistance:	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT4
IEEE Flammability:	1202

#### **Part Number**

Plenum (Y/N):	No

#### Variants

Item #	Color	Footnote
9365 0601000	CHROME	С
9365 0602500	CHROME	Z
9365 0605000	CHROME	С
9365 060U1000	CHROME	
9365 060U500	CHROME	

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

© 2018 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product tistelf or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.