

## Vinyl Cloth Adhesive Wire & Cable Wraps (B-498)

Printer automatically repeats your text to fill the label for maximum readability. Repositionable vinyl cloth material's special adhesive stays put, but marker can be removed and reapplied if necessary. Temp Range -40°F to 175°F (-40°C to 70°C). UL Recognized.




Figure 29



Fits Printer Models	Diagram	Catalog #	B#	Material	Color	Approx. Wire Gauge*	Max. Wire Dia. Inch (mm)	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels/Roll
BMP41, 51, 53	Fig. 29	M-7-498	B-498	Vinyl	BK on WT	22 - 16 Gauge	0.110 (2.8)	0.500 (12.7)	0.500 (12.7)	240
BMP41, 51, 53	Fig. 29	M-11-498	B-498	Vinyl	BK on WT	16 - 10 Gauge	0.160 (4.1)	0.750 (19.1)	0.500 (12.7)	220
BMP41, 51, 53	Fig. 29	M-48-498	B-498	Vinyl	BK on WT	12 - 10 Gauge	0.210 (5.3)	1.000 (25.4)	0.750 (19.1)	180
BMP41, 51, 53	Fig. 29	M-49-498	B-498	Vinyl	BK on WT	12 - 10 Gauge	0.210 (5.3)	1.000 (25.4)	1.000 (25.4)	160
BMP41, 51, 53	Fig. 29	M-131-498	B-498	Vinyl	BK on WT	10 - 4 Gauge	0.270 (6.7)	1.000 (25.4)	0.500 (12.7)	180
BMP41, 51, 53	Fig. 29	M-91-498	B-498	Vinyl	BK on WT	10 - 4 Gauge	0.270 (6.7)	1.500 (38.1)	1.000 (25.4)	120

## Patch Panel, Punch Block, Desi Strip and Faceplate Labels (B-412, and B-422)

Create a fully-formatted serialized punch block label to fit your equipment or label your ports, jacks and outlets with adhesive labels or slide-in strips.

**B-412 Polypropylene Tags** - Non-Adhesive Slide-in Strips

**B-422 Polyester Material** - Permanent adhesive, good for powder-coated/textured surfaces. Temp. Range: -40°F to 212°F (-40°C to 100°C). UL recognized.




Figure 29




Figure 33c



Fits Printer Models	Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Inch (mm)	Labels/Roll
<b>B-412 Polypropylene Tags</b>								
BMP41, 51, 53	Fig. 33c	MC-375-412	B-412	Polypropylene	BK on WT	0.375 (9.5)	20 ft (6.1 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33c	MC-475-412	B-412	Polypropylene	BK on WT	0.475 (12.1)	20 ft (6.1 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33c	MC-625-412	B-412	Polypropylene	BK on WT	0.625 (15.8)	20 ft (6.1 m)	1 roll (cont.)
<b>B-422 Polyester Material</b>								
BMP41, 51, 53	Fig. 33c	MC-375-422	B-422	Polyester	BK on WT	0.375 (9.5)	25 ft (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33c	MC-475-422	B-422	Polyester	BK on WT	0.475 (12.1)	25 ft (7.6 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 29	M-7-422	B-422	Polyester	BK on WT	0.500 (12.7)	0.500 (12.7)	280
BMP41, 51, 53	Fig. 29	M-89-422	B-422	Polyester	BK on WT	0.500 (12.7)	1.500 (38.1)	180
BMP41, 51, 53	Fig. 29	M-90-422	B-422	Polyester	BK on WT	0.750 (19.1)	1.500 (38.1)	180
BMP41, 51, 53	Fig. 29	M-47-422	B-422	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480

## Terminal Block Adhesive Strips (B-498)

When using terminal block mode, printer can serialize and pre-space to your special thin widths to fit terminal blocks.

**B-498 Repositionable Vinyl Cloth Material** - Special adhesive stays put, but marker can be removed and reapplied if necessary. Temp Range -40°F to 175°F (-40°C to 70°C). UL Recognized.





Figure 33c



Fits Printer Models	Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Inch (mm)	Labels/Roll
BMP41, 51, 53	Fig. 33c	MC-240-498	B-498	Vinyl	BK on WT	0.240 (6.1)	16 ft (4.9 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33c	MC-318-498	B-498	Vinyl	BK on WT	0.318 (8.1)	16 ft (4.9 m)	1 roll (cont.)
BMP41, 51, 53	Fig. 33c	MC-375-498	B-498	Vinyl	BK on WT	0.375 (9.5)	16 ft (4.9 m)	1 roll (cont.)