

# PermaSleeve® Wire Marking Sleeves

BradyID.com

## B-7641 PermaSleeve® Single-Sided Low Halogen Polyolefin Wire Marking Sleeves:

Use the table below to browse all available single-sided printing, 1.5" width B-7641 PermaSleeve® ZH Low Halogen Polyolefin Wire Marking Sleeves or build your own catalog number on page 190.

### Single-Sided Printable, 1.5" Sleeve Width

Catalog #	Color	Sleeves Per Roll	Approx. Wire Gauge	Range of Wire Diameter Inch (mm) Min. Max.	Supplied Diameter Inch (mm)	Recovered Diameter Inch (mm)	Recovered Wall Thickness Inch (mm)	Sleeve Width Inch (mm)	Rec. Printer	Rec. Ribbon
ZH-094-150-WT	White	2,500	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	.021 (0.5) ± .004 (0.1)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-094-150-WT-**	White	2,500	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	.021 (0.5) ± .004 (0.1)	--	PR Plus	R4300/ R6602
ZH-094-150-WT-S	White	500	24 to 20	0.047 (1.2) - 0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	.021 (0.5) ± .004 (0.1)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-125-150-WT	White	2,500	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	.025 (0.6) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-125-150-WT-**	White	2,500	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	.025 (0.6) ± .003 (0.07)	--	PR Plus	R4300/ R6602
ZH-125-150-WT-S	White	500	20 to 16	0.062 (1.6) - 0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	.025 (0.6) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-187-150-WT	White	2,500	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	.025 (0.6) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-187-150-WT-**	White	2,500	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	.025 (0.6) ± .003 (0.07)	--	PR Plus	R4300/ R6602
ZH-187-150-WT-S	White	500	16 to 10	0.094 (2.4) - 0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	.025 (0.6) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-250-150-WT	White	1,000	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	.029 (0.7) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-250-150-WT-**	White	1,000	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	.029 (0.7) ± .003 (0.07)	--	PR Plus	R4300/ R6602
ZH-250-150-WT-S	White	250	12 to 8	0.125 (3.2) - 0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	.029 (0.7) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-375-150-WT	White	1,000	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	.028 (0.7) ± .002 (0.05)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-375-150-WT-**	White	1,000	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	.028 (0.7) ± .002 (0.05)	--	PR Plus	R4300/ R6602
ZH-375-150-WT-S	White	250	8 to 4	0.188 (4.8) - 0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	.028 (0.7) ± .002 (0.05)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-500-150-WT	White	500	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	.028 (0.7) ± .002 (0.05)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-500-150-WT-**	White	500	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	.028 (0.7) ± .002 (0.05)	--	PR Plus	R4300/ R6602
ZH-500-150-WT-S	White	250	6 to 1	0.250 (6.4) - 0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	.028 (0.7) ± .002 (0.05)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-750-150-WT	White	250	2 to 4/0	0.375 (9.5) - 0.700 (17.8)	0.750 (19.0)	0.375 (9.5)	.031 (0.8) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-750-150-WT-**	White	250	2 to 4/0	0.375 (9.5) - 0.700 (17.8)	0.750 (19.0)	0.375 (9.5)	.031 (0.8) ± .003 (0.07)	--	PR Plus	R4300/ R6602
ZH-750-150-WT-S	White	100	2 to 4/0	0.375 (9.5) - 0.700 (17.8)	0.750 (19.0)	0.375 (9.5)	.031 (0.8) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-1000-150-WT	White	250	2/0 to 0.950" dia.	0.450 (11.4) - 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	.036 (0.9) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-1000-150-WT-**	White	250	2/0 to 0.950" dia.	0.450 (11.4) - 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	.036 (0.9) ± .003 (0.07)	--	PR Plus	R4300/ R6602
ZH-1000-150-WT-S	White	100	2/0 to 0.950" dia.	0.450 (11.4) - 0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	.036 (0.9) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-1500-150-WT	White	250	N/A	0.750 (19.0) - 1.400 (35.6)	1.500 (38.1)	0.752 (19.1)	.038 (1.0) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-1500-150-WT-S	White	100	N/A	0.750 (19.0) - 1.400 (35.6)	1.500 (38.1)	0.752 (19.1)	.038 (1.0) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-2000-150-WT	White	100	N/A	1.000 (25.4) - 1.900 (48.3)	2.000 (50.8)	1.000 (25.4)	.038 (1.0) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602
ZH-2000-150-WT-S	White	50	N/A	1.000 (25.4) - 1.900 (48.3)	2.000 (50.8)	1.000 (25.4)	.038 (1.0) ± .003 (0.07)	1.500 (38.1)	PR Plus	R4300/ R6602

#### \*Choosing Your PermaSleeve Color

While white and yellow are standard colors, you may special order your sleeves in the colors listed below. Replace WT or YL with the abbreviation of the desired color.

Example: ZH-094-2-WT-S becomes ZH-094-2-RD-S

#### Standard Stock Colors:

WT = White  
YL = Yellow

#### Special Order Colors:

(Contact Brady Customer Service for availability)

BK = Black      GY = Gray      RD = Red  
BL = Blue      OR = Orange      VT = Violet  
GR = Green

#### \*\* Choosing Your PermaSleeve Pieces (optional):

While 1 or 2 markers per sleeve is standard, you may also choose to have each sleeve slit multiple times to produce multiple pieces. Simply replace the double asterisks (\*\*) in the catalog number to fill in your desired pieces per marker.

Example: ZH-187-2-WT-S-\*\* becomes ZH-187-2-WT-S-4


This "4" means that this 2.000" sleeve is slit into four 0.500" pieces.

#### Standard Options:

1 or 2 markers per sleeve

#### Other Available Slit Options:

3 or 4 markers per sleeve  
(Contact Brady Customer Service for availability)



WT = White    YL = Yellow    BK = Black    BL = Blue    GR = Green    GY = Gray    OR = Orange    RD = Red    VT = Violet

Note: White and yellow are standard stock. All other colors available as special order.