

PermaSleeve® Wire Marking Sleeves

BradyID.com

B-7641 PermaSleeve® Double-Sided Low Halogen Polyolefin Wire Marking Sleeves:

Use the table below to browse all available double-sided printing, 2" width B-7641 PermaSleeve® 2ZH Low Halogen Polyolefin Wire Marking Sleeves or build your own catalog number on page 190.

Double-Sided Printable, 2" Sleeve Width

Catalog #	Color	Sleeves Per Roll	Approx. Wire Gauge	Range of Wire Diameter Inch (mm)		Supplied Diameter Inch (mm)	Recovered Diameter Inch (mm)	Recovered Wall Thickness Inch (mm)	Sleeve Width Inch (mm)	Rec. Printer	Rec. Ribbon
				Min.	Max.						
2LSZH-094-2-WT	White	2,500	24 to 20	0.047 (1.2)	0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	.021 (0.5) ± .004 (0.1)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-094-2-WT-**	White	2,500	24 to 20	0.047 (1.2)	0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	.021 (0.5) ± .004 (0.1)	--	PR Plus, BBP72	R4300/ R6602
2LSZH-094-2-WT-S	White	500	24 to 20	0.047 (1.2)	0.080 (2.0)	0.094 (2.4)	0.047 (1.2)	.021 (0.5) ± .004 (0.1)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-125-2-WT	White	2,500	20 to 16	0.062 (1.6)	0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	.025 (0.6) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-125-2-WT-**	White	2,500	20 to 16	0.062 (1.6)	0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	.025 (0.6) ± .003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2LSZH-125-2-WT-S	White	500	20 to 16	0.062 (1.6)	0.110 (2.8)	0.125 (3.2)	0.063 (1.6)	.025 (0.6) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-187-2-WT	White	2,500	16 to 10	0.094 (2.4)	0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	.025 (0.6) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-187-2-WT-**	White	2,500	16 to 10	0.094 (2.4)	0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	.025 (0.6) ± .003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2LSZH-187-2-WT-S	White	500	16 to 10	0.094 (2.4)	0.151 (3.8)	0.187 (4.8)	0.094 (2.4)	.025 (0.6) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-250-2-WT	White	1,000	12 to 8	0.125 (3.2)	0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	.029 (0.7) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-250-2-WT-**	White	1,000	12 to 8	0.125 (3.2)	0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	.029 (0.7) ± .003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2LSZH-250-2-WT-S	White	250	12 to 8	0.125 (3.2)	0.215 (5.5)	0.250 (6.4)	0.126 (3.2)	.029 (0.7) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-375-2-WT	White	1,000	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	.028 (0.7) ± .002 (0.05)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-375-2-WT-**	White	1,000	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	.028 (0.7) ± .002 (0.05)	--	PR Plus, BBP72	R4300/ R6602
2LSZH-375-2-WT-S	White	250	8 to 4	0.188 (4.8)	0.320 (8.1)	0.375 (9.5)	0.189 (4.8)	.028 (0.7) ± .002 (0.05)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-500-2-WT	White	500	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	.028 (0.7) ± .002 (0.05)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-500-2-WT-**	White	500	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	.028 (0.7) ± .002 (0.05)	--	PR Plus, BBP72	R4300/ R6602
2LSZH-500-2-WT-S	White	250	6 to 1	0.250 (6.4)	0.450 (11.4)	0.500 (12.7)	0.252 (6.4)	.028 (0.7) ± .002 (0.05)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-750-2-WT	White	250	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.375 (9.5)	.031 (0.8) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-750-2-WT-**	White	250	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.375 (9.5)	.031 (0.8) ± .003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2LSZH-750-2-WT-S	White	100	2 to 4/0	0.375 (9.5)	0.700 (17.8)	0.750 (19.0)	0.375 (9.5)	.031 (0.8) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-1000-2-WT	White	250	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	.036 (0.9) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-1000-2-WT-**	White	250	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	.036 (0.9) ± .003 (0.07)	--	PR Plus, BBP72	R4300/ R6602
2LSZH-1000-2-WT-S	White	100	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	.036 (0.9) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-1500-2-WT	White	250	N/A	0.750 (19.0)	1.400 (35.6)	1.500 (38.1)	0.752 (19.1)	.038 (1.0) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-1500-2-WT-S	White	100	N/A	0.750 (19.0)	1.400 (35.6)	1.500 (38.1)	0.752 (19.1)	.038 (1.0) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-2000-2-WT	White	100	N/A	1.000 (25.4)	1.900 (48.3)	2.000 (50.8)	1.000 (25.4)	.038 (1.0) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602
2LSZH-2000-2-WT-S	White	50	N/A	1.000 (25.4)	1.900 (48.3)	2.000 (50.8)	1.000 (25.4)	.038 (1.0) ± .003 (0.07)	2.000 (50.8)	PR Plus, BBP72	R4300/ R6602

B-7641 PermaSleeve® Single-Sided Low Halogen Polyolefin Wire Marking Sleeves:

Use the table below to browse all available single-sided printing 3" width B-7641 PermaSleeve® ZH Low Halogen Polyolefin Wire Marking Sleeves or build your own catalog number on page 190.

Single-Sided Printable, 3" Sleeve Width

Catalog #	Color	Sleeves Per Roll	Approx. Wire Gauge	Range of Wire Diameter Inch (mm)		Supplied Diameter Inch (mm)	Recovered Diameter Inch (mm)	Recovered Wall Thickness Inch (mm)	Sleeve Width Inch (mm)	Rec. Printer	Rec. Ribbon
				Min.	Max.						
ZH-1000-3-WT	White	250	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	.036 (0.9) ± .003 (0.07)	3.000 (76.2)	PR Plus	R4300/ R6602
ZH-1000-3-YL	Yellow	250	2/0 to 0.950" dia.	0.450 (11.4)	0.950 (24.1)	1.000 (25.4)	0.500 (12.7)	.036 (0.9) ± .003 (0.07)	3.000 (76.2)	PR Plus	R4300/ R6602
ZH-1500-3-WT	White	250	N/A	0.750 (19.0)	1.400 (35.6)	1.500 (38.1)	0.752 (19.1)	.038 (1.0) ± .003 (0.07)	3.000 (76.2)	PR Plus	R4300/ R6602
ZH-1500-3-YL	Yellow	250	N/A	0.750 (19.0)	1.400 (35.6)	1.500 (38.1)	0.752 (19.1)	.038 (1.0) ± .003 (0.07)	3.000 (76.2)	PR Plus	R4300/ R6602
LSZH-2000-3-WT	White	100	N/A	1.000 (25.4)	1.900 (48.3)	2.000 (50.8)	1.000 (25.4)	.038 (1.0) ± .003 (0.07)	3.000 (76.2)	PR Plus	R4300/ R6602
LSZH-2000-3-YL	Yellow	100	N/A	1.000 (25.4)	1.900 (48.3)	2.000 (50.8)	1.000 (25.4)	.038 (1.0) ± .003 (0.07)	3.000 (76.2)	PR Plus	R4300/ R6602

IP Series, PR Plus & BBP72 Print Ribbons on page 134
Full Material Properties on page 227.