

Dot Matrix Materials - Portables

BradyID.com

Dot Matrix / Laser / Ink Jet

Permasleeve® Wire Marking Sleeves




Figure 21



Printer Model(s)	Diagram	Part Number	B-#	Color	Approx Wire Gauge	Minimum Wire Dia.	Maximum Wire Dia.	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Row	Labels Per Pkg	Rec. Ribbon
LS	Fig. 21	PS-0231-094-WT	B-342	White	28-18	0.023 (0.58)	0.080 (2.03)	2.000 (50.8)	0.182 (4.62)	2	500	
LS, XC	Fig. 21	PSBXP-111-125	B-342	White	22-16	0.046 (1.17)	0.110 (2.79)	1.000 (25.4)	0.235 (6.00)	1	500	
LS, XC	Fig. 21	PSBXP-114-125	B-342	White	22-16	0.046 (1.17)	0.110 (2.79)	1.250 (31.75)	0.235 (6.00)	1	500	
LS	Fig. 21	PS-0231-125-WT	B-342	White	22-16	0.046 (1.17)	0.110 (2.79)	2.000 (50.8)	0.235 (6.00)	3	500	
LS, XC	Fig. 21	PSBXP-111-187	B-342	White	18-12	0.062 (1.57)	0.150 (3.81)	1.000 (25.4)	0.335 (8.50)	1	500	
LS, XC	Fig. 21	PSBXP-114-187	B-342	White	18-12	0.062 (1.57)	0.150 (3.81)	1.250 (31.75)	0.335 (8.50)	1	500	
LS	Fig. 21	PS-0331-187-WT	B-342	White	18-12	0.062 (1.57)	0.150 (3.81)	2.000 (50.8)	0.335 (8.50)	4	500	
LS, XC	Fig. 21	PSBXP-211-250	B-342	White	16-10	0.094 (2.39)	0.215 (5.46)	1.000 (25.4)	0.439 (11.20)	1	500	
LS, XC	Fig. 21	PSBXP-214-250	B-342	White	16-10	0.094 (2.39)	0.215 (5.46)	1.250 (31.75)	0.439 (11.20)	1	500	
LS	Fig. 21	PS-0531-250-WT	B-342	White	16-10	0.094 (2.39)	0.215 (5.46)	2.000 (50.8)	0.439 (11.20)	5	500	
LS	Fig. 21	PS-2231-1000-WT	B-342	White	1-500	0.450 (11.43)	0.950 (24.13)	2.000 (50.8)	1.660 (42.16)	8	100	Rec. Ribbon for all parts: R4300, R4502S, R5000, R6600, R6700
LS, XC	Fig. 21	PSBXP-311-375	B-342	White	12-6	0.125 (3.18)	0.320 (8.13)	1.000 (25.4)	0.645 (16.38)	1	250	
LS, XC	Fig. 21	PSBXP-314-375	B-342	White	12-6	0.125 (3.18)	0.320 (8.13)	1.250 (31.75)	0.645 (16.38)	1	250	
LS	Fig. 21	PS-0831-375-WT	B-342	White	12-6	0.125 (3.18)	0.320 (8.13)	2.000 (50.8)	0.645 (16.38)	6	250	
LS, XC	Fig. 21	PSBXP-411-500	B-342	White	8-1	0.187 (4.75)	0.450 (11.43)	1.000 (25.4)	0.851 (21.62)	1	250	
LS, XC	Fig. 21	PSBXP-414-500	B-342	White	8-1	0.187 (4.75)	0.450 (11.43)	1.250 (31.75)	0.851 (21.62)	1	250	
LS	Fig. 21	PS-1031-500-WT	B-342	White	8-1	0.187 (4.75)	0.450 (11.43)	2.000 (50.8)	0.851 (21.62)	7	250	
LS	Fig. 21	PS-0231-094-YL	B-342	Yellow	28-18	0.023 (0.58)	0.080 (2.03)	2.000 (50.8)	0.182 (4.62)	9	500	
LS	Fig. 21	PS-0231-125-YL	B-342	Yellow	22-16	0.046 (1.17)	0.110 (2.79)	2.000 (50.8)	0.235 (6.00)	10	500	
LS	Fig. 21	PS-0331-187-YL	B-342	Yellow	18-12	0.062 (1.57)	0.150 (3.81)	2.000 (50.8)	0.335 (8.50)	11	500	
LS	Fig. 21	PS-0531-250-YL	B-342	Yellow	16-10	0.094 (2.39)	0.215 (5.46)	2.000 (50.8)	0.439 (11.20)	12	500	
LS	Fig. 21	PS-2231-1000-YL	B-342	Yellow	1-500	0.450 (11.43)	0.950 (24.13)	2.000 (50.8)	1.660 (42.16)	15	100	
LS	Fig. 21	PS-0831-375-YL	B-342	Yellow	12-6	0.125 (3.18)	0.320 (8.13)	2.000 (50.8)	0.645 (16.38)	13	250	
LS	Fig. 21	PS-1031-500-YL	B-342	Yellow	8-1	0.187 (4.75)	0.450 (11.43)	2.000 (50.8)	0.851 (21.62)	14	250	

BRADYSLEEVE™ Wire Marking Sleeves Heat-Shrink and Non-Shrink Sleeves




Figure 36

Printer Model(s)	Diagram	Part Number	B-#	Material	Color	Approx Wire Gauge	Minimum Wire Dia.	Maximum Wire Dia.	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Row	Labels Per Pkg	Rec. Ribbon
Heat-Shrink Sleeves													
ID, LS, XC	Fig. 36	WMS-105-321	B-321	Polyolefin	White	18-12	0.075 (1.90)	0.130 (3.30)	0.500 (12.7)	0.350 (8.90)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-111-321	B-321	Polyolefin	White	18-12	0.075 (1.90)	0.130 (3.30)	1.000 (25.4)	0.350 (8.90)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-117-321	B-321	Polyolefin	White	18-12	0.075 (1.90)	0.130 (3.30)	1.500 (38.1)	0.350 (8.90)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-205-321	B-321	Polyolefin	White	10-8	0.130 (3.30)	0.235 (6.00)	0.500 (12.7)	0.500 (12.7)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-211-321	B-321	Polyolefin	White	10-8	0.130 (3.30)	0.235 (6.00)	1.000 (25.4)	0.500 (12.7)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-217-321	B-321	Polyolefin	White	10-8	0.130 (3.30)	0.235 (6.00)	1.500 (38.1)	0.500 (12.7)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-411-321	B-321	Polyolefin	White	6-3	0.235 (6.00)	0.375 (9.53)	1.000 (25.4)	0.750 (19.05)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-417-321	B-321	Polyolefin	White	6-3	0.235 (6.00)	0.375 (9.53)	1.500 (38.1)	0.750 (19.05)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-611-321	B-321	Polyolefin	White	2-0	0.375 (9.53)	0.540 (13.72)	1.000 (25.4)	1.000 (25.4)	1	250	R2000, R5000
ID, LS, XC	Fig. 36	WMS-617-321	B-321	Polyolefin	White	2-0	0.375 (9.53)	0.540 (13.72)	1.500 (38.1)	1.000 (25.4)	1	250	R2000, R5000
Non-Shrink Sleeves													
ID, LS, XC	Fig. 36	WMS-105-319	B-319	Polyolefin	White	18-12	0.075 (1.90)	0.130 (3.30)	0.500 (12.7)	0.350 (8.90)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-111-319	B-319	Polyolefin	White	18-12	0.075 (1.90)	0.130 (3.30)	1.000 (25.4)	0.350 (8.90)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-117-319	B-319	Polyolefin	White	18-12	0.075 (1.90)	0.130 (3.30)	1.500 (38.1)	0.350 (8.90)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-205-319	B-319	Polyolefin	White	10-8	0.130 (3.30)	0.235 (6.00)	0.500 (12.7)	0.500 (12.7)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-211-319	B-319	Polyolefin	White	10-8	0.130 (3.30)	0.235 (6.00)	1.000 (25.4)	0.500 (12.7)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-217-319	B-319	Polyolefin	White	10-8	0.130 (3.30)	0.235 (6.00)	1.500 (38.1)	0.500 (12.7)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-411-319	B-319	Polyolefin	White	6-3	0.235 (6.00)	0.375 (9.53)	1.000 (25.4)	0.750 (19.05)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-417-319	B-319	Polyolefin	White	6-3	0.235 (6.00)	0.375 (9.53)	1.500 (38.1)	0.750 (19.05)	1	500	R2000, R5000
ID, LS, XC	Fig. 36	WMS-611-319	B-319	Polyolefin	White	2-0	0.375 (9.53)	0.540 (13.72)	1.000 (25.4)	1.000 (25.4)	1	250	R2000, R5000
ID, LS, XC	Fig. 36	WMS-617-319	B-319	Polyolefin	White	2-0	0.375 (9.53)	0.540 (13.72)	1.500 (38.1)	1.000 (25.4)	1	250	R2000, R5000

Full Material Properties on page 237.

Dot Matrix - Portables