

TLS 2200® Wire & Cable Materials

BradyID.com/tls2200

Portable Printers



TLS 2200® Wire & Cable ID Materials

Brady's wire and cable identification products include wire labels, heat-shrinkable sleeves, tags, and other cable marking products.

Lab and field tested, Brady's wire and cable identification products are proven to withstand harsh environments, including extreme temperatures, liquids, abrasion and more.

Cable marking solutions are available in a variety of sizes and colors to ensure that your wires and cables are marked with clear, legible identification.

Printer Compatibility

All wire and cable materials on the following pages are only compatible with:



TLS 2200® Label Printer

See Page 26



TLS PC Link™ Printer

See Page 27

B-109 Polyethylene Tag Material

Color: White Finish: Matte

Excellent multi-purpose tag for identifying multiconductor cables, inventory, safety warning repair and work-in-processing manufacturing. Good weatherability, humidity resistance and legibility after solvent exposure.

Performance Attributes: 




Figure 45




Figure 56



Diagram	Part Number	B-#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Row	Labels Per Pkg	Rec. Ribbon
Fig. 45	PTL-36-109	B-109	Polyethylene	White	1.125 (28.6)	1.750 (44.5)	1	250	R4310
Fig. 56	PTL-12-109	B-109	Polyethylene	White	3.000 (76.2)	0.750 (19.1)	1	100	R4310
Fig. 56	BM71-12-109	B-109	Polyethylene	White	3.000 (76.2)	0.750 (19.1)	1	1000	R4310

B-145 Polyethylene Tag Material

Color: Gray Finish: Matte

Multipurpose material for tag applications. Ideal for identifying multiconductor cables, inventory, equipment, lockout, safety warning repair and work-in-progress.

Performance Attributes: 




Figure 50



Diagram	Part Number	B-#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Row	Labels Per Pkg	Rec. Ribbon
Fig. 50	PTL-111-145-GY	B-145	Polyethylene	Gray	1.206 (30.6)	0.758 (19.3)	1	100	R6210
Fig. 50	BM71-111-145-GY	B-145	Polyethylene	Gray	1.206 (30.6)	0.758 (19.3)	1	1000	R6210
Fig. 50	PTL-110-145-GY	B-145	Polyethylene	Gray	1.750 (44.5)	1.000 (25.4)	1	100	R6210
Fig. 50	BM71-110-145-GY	B-145	Polyethylene	Gray	1.750 (44.5)	1.000 (25.4)	1	1000	R6210
Flame Retardant B-145 Polyethylene Tag Material									
Fig. 50	PTL-111-145FR-GY	B-145	Polyethylene	Gray	1.206 (30.6)	0.758 (19.3)	1	100	R6210
Fig. 50	BM71-111-145FR-GY	B-145	Polyethylene	Gray	1.206 (30.6)	0.758 (19.3)	1	1,000	R6210
Fig. 50	PTL-110-145FR-GY	B-145	Polyethylene	Gray	1.750 (44.5)	1.000 (25.4)	1	100	R6210
Fig. 50	BM71-110-145FR-GY	B-145	Polyethylene	Gray	1.750 (44.5)	1.000 (25.4)	1	1,000	R6210

* FR designates Flame Retardant

TLS 2200 Wire & Cable