# **BMP®41 Label Printer**

### BradyID.com/bmp41



#### **Printer Demo Video**

Visit BradyID.com/bmp41 for more information or to view an online printer demo video.

BMP41 cartridges with
label and print ribbon

bel and print ribbonpage 11	
-----------------------------	--

#### **BMP®41 Label Printer & Accessories**

Catalog #	Description
BMP41	BMP41 Label Printer with Hard Case*
BMP41-KIT-VD	BMP41 Printer DataComm Starter Kit*
BMP41-KIT-EL	BMP41 Printer Electrical Starter Kit*
BMP41-KIT-GI	BMP41 Printer Facility ID Starter Kit*
BMP41-BATT	BMP41 Rechargeable Battery Pack
BMP41-QC	BMP41 External Battery Quick Charger
BMP41-AC	BMP41 AC Adapter / Battery Charger
BMP41-MAGNET	BMP41 Magnet Accessory
BMP41-HC	BMP41 Hard Case
BMP41-USB	BMP41 USB Cable

\*Printer ships with BMP41 printer, NiMH battery, AC adapter / charger, hard case, MC1-1000-595-WT-BK cartridge, USB cable, product & drivers CD, quick start guide and 2-year warranty.

A108 Electrical

Labeling

**BMP**<sup>®</sup>41 LABEL PRINTER

#### ONE AND DONE. BMP®41 Printer Does It All!

A rugged, handheld labeling solution that gives you the versatility of die-cut labels and continuous labels in one printer!

- Quick-load, drop-in cartridges for quick supply change and automatic label formatting
- Fast print speed of 1.3" per second
- Over 100 label parts in 11 materials
- 3/4" sleeves and 1" wide continuous output
- Drop tested rugged industrial bumpers with a grab and go grip to be on the move with you
- Large graphical LCD display with backlight to see exactly what you're printing
- Rechargeable NiMH battery or AC adapter, for long lasting power supply
- Built-in wizard-style apps for wire ID, cabel flags, terminal blocks, patch panels, breaker boxes and general ID





BMP®41 Printer S	pecifications
Max Labels Per	Average 250 labels/day
Day	Average 200 labels/day
Print Resolution	300 dpi
Print Technology	Thermal transfer
Print Speed	33mm/sec (1.3in/sec)
Tape Widths	Various sizes from
(inches)	0.235" to 1.0"
Tape Widths	Various sizes from
(mm)	5.969 mm to 25.4 mm
Max Label Width	1.00" (25.4mm)
Max Print Width	0.96" (24.4 mm)
	48 MB / Up to 25,000
Memory	Labels
Materials	M-, MC-, MC1- Series
Supported	Cartridges (1.00" and 0.75" height only)
Supported	100+ Stock Parts
Continuous vs	Continuous and die cut
Die Cut Labels	labels
Connectivity	
Options	Yes
PC Connectivity	USB
Software	
	Optional through USB
Compatibility	Yes - with Labelmark®
File Transfer from PC to printer	Software
	Soliware
Wireless	No
Connectivity	
Stand Alone	Yes
Printing	
Color Capability	Single print color on a label
Keyboard	QWERTY
Backlit Screen	2.5" x 1.4", user adjustable
2401411 0010011	backlit
Text Sizes	4 to 103pt + autosizing
Multi-Line Print	Yes
Print Rotation	Yes
Serialization	Yes
Barcode	39 and 128
Symbols	
Categories	450
Portability	Yes
,	Adhesive Polyester,
	PermaSleeve® Heat Shrink
	Tubing, Polypropylene
Label Types or	Tags, Self-laminating Vinyl,
Application	Metallized Polyester Ultra
Functions	Aggressive Polyester,
	Repositional Vinnl Cloth,
	Nylon Cloth, Reflective
	Tape, Indoor/Outdoor Vinyl,
	Basic and Die Cut labels
	for Wire and Cable ID, Datacomm and AV
Applications	labeling, Electrical ID, Pane
Applications	ID, Product ID, Facility ID,
	Safety and Maintenance,
	General ID
	AC Power, rechargable
Power Supply	NiMH battery
	NiMH battery
Power Supply Weight Warranty	NiMH battery 2.6 lbs (1.2 kg) 2 years

### Exceptional material variety and durability.



Equipment Labeling



Self-Laminating I abels Communications





#### PermaSleeve Wire Marking

	сен1118
N	4
In	door / Outdoor Vinvl

Labels...and more!

**BMP®41** Printer

I

10

## BRADY WHEN PERFORMANCE MATTERS MOST