

# PermaSleeve® Wire Marking Sleeves

BradyID.com

## Single-Sided Printable, 2" Sleeve Width

(Continued from previous page.)

| Catalog #         | Color | Sleeves Per Roll | Approx. Wire Gauge | Range of Wire Diameter Inch (mm) |                | Supplied Diameter Inch (mm) | Recovered Diameter Inch (mm) | Recovered Wall Thickness Inch (mm) | Sleeve Width Inch (mm) | Rec. Printer | Rec. Ribbon  |
|-------------------|-------|------------------|--------------------|----------------------------------|----------------|-----------------------------|------------------------------|------------------------------------|------------------------|--------------|--------------|
|                   |       |                  |                    | Min.                             | Max.           |                             |                              |                                    |                        |              |              |
| HX-750-2-WT       | White | 250              | 2 to 4/0           | 0.375 (9.5)                      | - 0.700 (17.8) | 0.750 (19.0)                | 0.374 (9.5)                  | 0.030 (0.8) ± 0.003 (0.07)         | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-750-2-WT-**    | White | 250              | 2 to 4/0           | 0.375 (9.5)                      | - 0.700 (17.8) | 0.750 (19.0)                | 0.374 (9.5)                  | 0.030 (0.8) ± 0.003 (0.07)         | --                     | PR Plus      | R4300/ R6602 |
| HX-750-2-WT-S     | White | 100              | 2 to 4/0           | 0.375 (9.5)                      | - 0.700 (17.8) | 0.750 (19.0)                | 0.374 (9.5)                  | 0.030 (0.8) ± 0.003 (0.07)         | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-750-2-WT-J     | White | 2,500            | 2 to 4/0           | 0.375 (9.5)                      | - 0.700 (17.8) | 0.750 (19.0)                | 0.374 (9.5)                  | 0.030 (0.8) ± 0.003 (0.07)         | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-750-2-WT-J-**  | White | 2,500            | 2 to 4/0           | 0.375 (9.5)                      | - 0.700 (17.8) | 0.750 (19.0)                | 0.374 (9.5)                  | 0.030 (0.8) ± 0.003 (0.07)         | --                     | PR Plus      | R4300/ R6602 |
| HX-1000-2-WT      | White | 250              | 2/0 to 0.950" dia. | 0.450 (11.4)                     | - 0.950 (24.1) | 1.000 (25.4)                | 0.500 (12.7)                 | 0.035 (0.9) ± 0.005 (0.1)          | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-1000-2-WT-**   | White | 250              | 2/0 to 0.950" dia. | 0.450 (11.4)                     | - 0.950 (24.1) | 1.000 (25.4)                | 0.500 (12.7)                 | 0.035 (0.9) ± 0.005 (0.1)          | --                     | PR Plus      | R4300/ R6602 |
| HX-1000-2-WT-S    | White | 100              | 2/0 to 0.950" dia. | 0.450 (11.4)                     | - 0.950 (24.1) | 1.000 (25.4)                | 0.500 (12.7)                 | 0.035 (0.9) ± 0.005 (0.1)          | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-1000-2-WT-J    | White | 2,500            | 2/0 to 0.950" dia. | 0.450 (11.4)                     | - 0.950 (24.1) | 1.000 (25.4)                | 0.500 (12.7)                 | 0.035 (0.9) ± 0.005 (0.1)          | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-1000-2-WT-J-** | White | 2,500            | 2/0 to 0.950" dia. | 0.450 (11.4)                     | - 0.950 (24.1) | 1.000 (25.4)                | 0.500 (12.7)                 | 0.035 (0.9) ± 0.005 (0.1)          | --                     | PR Plus      | R4300/ R6602 |
| HX-1500-2-WT      | White | 250              | N/A                | 0.750 (19.0)                     | - 1.400 (35.6) | 1.500 (38.1)                | 0.752 (19.1)                 | 0.040 (1.0) ± 0.006 (0.2)          | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-1500-2-WT-S    | White | 100              | N/A                | 0.750 (19.0)                     | - 1.400 (35.6) | 1.500 (38.1)                | 0.752 (19.1)                 | 0.040 (1.0) ± 0.006 (0.2)          | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-1500-2-WT-J    | White | 1,000            | N/A                | 0.750 (19.0)                     | - 1.400 (35.6) | 1.500 (38.1)                | 0.752 (19.1)                 | 0.040 (1.0) ± 0.006 (0.2)          | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-2000-2-WT      | White | 100              | N/A                | 1.000 (25.4)                     | - 1.900 (48.3) | 2.000 (50.8)                | 1.000 (25.4)                 | 0.045 (1.1) ± 0.007 (0.2)          | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-2000-2-WT-S    | White | 50               | N/A                | 1.000 (25.4)                     | - 1.900 (48.3) | 2.000 (50.8)                | 1.000 (25.4)                 | 0.045 (1.1) ± 0.007 (0.2)          | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |
| HX-2000-2-WT-J    | White | 1,000            | N/A                | 1.000 (25.4)                     | - 1.900 (48.3) | 2.000 (50.8)                | 1.000 (25.4)                 | 0.045 (1.1) ± 0.007 (0.2)          | 2.000 (50.8)           | PR Plus      | R4300/ R6602 |

### \*Choosing Your PermaSleeve Color

While white is a standard color, additional colored sleeves are available as custom parts as well. Simply replace "WT" with the abbreviation of the desired color to order.

Example: HX-094-150-WT-4 becomes HX-094-150-RD-4

**Available Colors:** (Contact Brady Customer Service for availability)

WT = White    BL = Blue    GY = Gray    RD = Red    YL = Yellow  
 BK = Black    GR = Green    OR = Orange    VT = Violet

### \*\* Choosing Your PermaSleeve Pieces (optional):

While 1 or 2 markers per sleeve is standard, you may also choose to have each sleeve slit multiple times to produce multiple pieces. Simply replace the double asterisks (\*\*) in the catalog number to fill in your desired pieces per marker.

Example: HX-187-150-WT-\*\* becomes HX-187-150-WT-4  
 This "4" means that this 2.000" sleeve is slit into four 0.500" pieces.

**Standard Option:**  
 1 or 2 markers per sleeve

**Other Available Slit Options:**  
 3 or 4 markers per sleeve



## Can't Find The PermaSleeve You Need? Build Your Own Part Number!

Use the "Assemble Your Own PermaSleeve" guide on page 194 to quickly and easily assemble the right B-7642 PermaSleeve HX Wire Marking Sleeve for your application.

Need additional help? Contact Brady Customer Service at 1-888-272-3946 for more information or to order.

### Follow the steps on page 194 to quickly identify:

- Single or Double Sided Sleeves
- Sleeve Width
- Wire Diameter Requirements
- Color & Roll Size
- Additional Slits