

# IDXPERT™ Label Materials

BradyID.com



The IDXPERT™ printer has been discontinued, but Brady continues to manufacture and stock labels and accessories for the printer!

Catalog #	Description
XPERT-HC-ABC	Hard Case for ABC Layout
XPERT-HC-KEY	Hard Case for KEYBOARD Layout
LABXPERT-SER-USB	Serial-to-USB adapter for PC cable
PCK-6	Cleaning Kit

## Labels for Lean, Facility & Safety ID and General ID. (B-422, B-428, B-483, B-499, B-595)

**B-422 Polyester Material** - Permanent adhesive, good for powder-coated/textured surfaces. Best on flat surfaces. Temp. Range: -40°F to 212°F (-40°C to 100°C). UL recognized.

**B-428 Metallized Polyester Material** - Permanent adhesive, silver finish. Temp. Range: -40°F to 176°F (-40°C to 80°C). UL recognized.

**B-483 Polyester Material** - Permanent adhesive for powder-coated/textured surfaces. Best on flat surfaces. Temp. Range: -40°F to 248°F (-40°C to 120°C). UL recognized.

**B-499 Nylon Cloth Material** - Permanent adhesive. Pliable for rough or smooth surfaces. Temp. Range: -94°F to 194°F (-70°C to 90°C). UL recognized.

**B-595 Indoor/Outdoor Vinyl Material** - Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. Range: -40°F to 180°F (-40°C to 82°C). UL recognized.




Figure 29



Figure 33




Figure 46  
(Includes black border)

Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Inch (mm)	Labels/Roll	Price
<b>B-422 Polyester Labels</b>								
Fig. 29	X-7-422	B-422	Polyester	BK on WT	0.500 (12.7)	0.500 (12.7)	350	
Fig. 29	X-19-422	B-422	Polyester	BK on WT	1.000 (25.4)	1.000 (25.4)	250	
Fig. 29	X-132-422	B-422	Polyester	BK on WT	1.500 (38.1)	1.250 (31.8)	250	
Fig. 29	X-30-422	B-422	Polyester	BK on WT	1.500 (38.1)	0.750 (19.1)	250	
<b>B-428 Metallized Polyester Labels</b>								
Fig. 29	X-17-428-SV-BK	B-428	Polyester	BK on SV	1.000 (25.4)	0.500 (12.7)	500	
Fig. 46	X-24-428-SVBB-BK	B-428	Polyester	BK on SV	1.130 (28.7)	0.500 (12.7)	500	
Fig. 29	X-29-428-SV-BK	B-428	Polyester	BK on SV	1.500 (38.1)	0.500 (12.7)	500	
Fig. 29	X-30-428-SV-BK	B-428	Polyester	BK on SV	1.500 (38.1)	0.750 (19.1)	325	
Fig. 29	X-20-428-SV-BK	B-428	Polyester	BK on SV	2.000 (50.8)	1.000 (25.4)	100	

General ID labels continued on next page.