

Part Number: C2528A

Revision Level: 5

Date: 7/31/2007

3C 20 7/28 TC PE OAS PVC

COMMUNICATION CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#20 AWG 7/28 Tinned Copper	0.038" nom.
Insulation:	0.016" Wall Polyethylene	0.070" nom.
Cable:	3 conductors @ 2.00" LHL with alum./polyester (foil out) & #22 7/30 Tinned Copper drain wire.	0.150" nom.
Jacket:	0.030" Wall Polyvinyl Chloride	0.210" +/- 0.011"
Print Legend:	<i>CAROL (R) -- C2528A -- 75C E111240-8 CM (UL) C (UL) CMH OR AWM STYLE 2093 -- MADE IN USA (DATE CODE)</i>	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2093
Canadian Standards Association	Type CMH

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75 C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	10.3 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	21 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	37.5 pF/ft @ 1kHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red
3	Natural