



PRODUCT INFORMATION:

- 1.) DATATUFF CAT 5E 24AWG SOLID BARE COPPER CONDUCTORS
- 2.) BONDED PAIRS
- 3.) 600V AWM RATED
- 4.) ALUMINUM/POLYESTER F/UTP SHIELD WITH A 24AWG STRANDED TINNED COPPER DRAIN WIRE
- 5.) INDUSTRIAL GRADE SUNLIGHT, OIL/WATER RESISTANT, CMR/CMX BLACK JACKET
- 6.) OPERATING TEMP RANGE -40C TO +75C
- 7.) STRAIN RELIEF BOOTS INSTALLED ON EACH END

PINOUT		
RJ45S		RJ45S
CASE	DRAIN	CASE
1	WH/OR	1
2	OR/WH	2
3	WH/GN	3
4	BL/WH	4
5	WH/BL	5
6	GN/WH	6
7	WH/BR	7
8	BR/WH	8



FILE NAME
CONTRACT NO N/A
DRAWN 11/20/19 RAYT
CHECK 11/20/19 JOSH W
APPR. 11/20/19 JOSH W
ISSUED 11/20/19 RAYT

CUSTOMER SPEC			
C271893BK			
RJ45S/45S DATATUFF 5E 600V			
SIZE	FSCM NO	DWG NO	REV
C		C271893BK	A
SCALE	N/A	WEIGHT	N/A
		SHEET	1 OF 1