

Part Number: C6348A

Revision Level: 6

Date: 7/16/2007

2C 22 7/30 TC SR-PVC PVC

COMMUNICATION CABLE

A. CONSTRUCTION

Conductor:	#22 AWG 7/30 Tinned Copper	0.030" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.050" nom.
Cable:	2 conductors	0.100" nom.
Jacket:	0.015" Wall Polyvinyl Chloride	0.130" +/- 0.007"
Print Legend:	<i>CAROL (R) 22 AWG -- C6348A -- 75C 111240-8 CM (UL) C (UL) --- CSA LL69381 CMG -- MADE IN USA (DATE CODE)</i>	

DIAMETERS

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	16 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	24.5 pF/ft @ 1kHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	Red