



# CABLE TECHNOLOGY, INC.

73 RIVER ROAD - WILLINGTON, CT 06279 - (860) 429 - 7889 FAX (860) 429 - 3615



## CT-E421I BELDEN 9534 EQUAL

---

<u>CONDUCTORS:</u>	#24 7/32 TC INSULATED WITH .010" PVC
<u>CABLING:</u>	CABLE FOUR (4) CONDUCTORS TOGETHER WITH A #24 7/32 TC DRAIN WIRE
<u>TAPE SHIELD:</u>	WRAP WITH AN ALUMINUM/POLYESTER TAPE SHIELD, FOIL FACING IN
<u>JACKET:</u>	.035" CHROME PVC
<u>NOM OD:</u>	.184"
<u>PRINT IN WHITE:</u> (1426)	E151405 24 AWG TYPE CM 105°C (UL) VW-1...AWM 2464...C(UL) 105°C 300V TYPE CMG ...CE...ROHS
<u>UV RESISTANT:</u>	YES
<u>COLOR CODE:</u>	1) BLACK 2) WHITE 3) RED 4) GREEN
NOM. CAPACITANCE CONDUCTOR TO CONDUCTOR:	33 PF/FT
NOM. CAPACITANCE COND. TO OTHER CONDUCTOR & SHIELD:	65 PF/FT
NOM. CONDUCTOR DC RESISTANCE:	25 DCR @ 20°C (OHM/1000 FT)
NOMINAL OUTER SHIELD DC RESISTANCE:	18 DCR @ 20°C (OHM/1000 FT)
MAX. OPERATING VOLTAGE - UL:	300V RMS
MAX. RECOMMENDED CURRENT:	1.75 AMPS PER CONDUCTOR @ 25°C