


[Home](#)
[About Us](#)
[News](#)
[Products](#)
[Locations](#)
[Contact Us](#)

Products

Browse Products

 Select Metal Type:

 Select Construction Category:

Nickel Plated Copper (ASTM B355) > Tubular Braid

NICKEL PLATED COPPER TUBULAR BRAID

Made in compliance with AA59569 (formerly QQB575) specifications where applicable. The braid is manufactured to provide shield coverage of 90% minimum (70% for .078" and smaller) at the nominal diameters specified. The raw material meets ASTM B355 requirements.

Part No.	AA59569	Nominal I.D.	AWG of Individual Ends	No. of Strands (Carriers)	No. of Wires per Strand	Total No. of Wires	Approx. AWG Equivalent	Nom. Circular Mills	Approx. Shipping Weight (Lbs/1000 Ft)
110N	AA59569R32N0062	1/16"	32	16	1	16	20	1,011	6
112N	AA59569R32N0109	7/64"	32	16	2	32	17	2,023	9
114N	AA59569R32N0125	1/8"	32	24	2	48	15	3,034	13
116N	AA59569R32N0171	11/64"	32	24	3	72	14	4,551	18
118N	AA59569R32N0203	13/64"	32	24	5	120	11	7,585	28
120N	AA59569R32N0375	3/8"	32	48	3	144	11	9,102	38
122N	AA59569R32N0500	1/2"	32	48	4	192	9	12,136	45
124N	AA59569R32N0781	25/32"	32	48	7	336	7	21,239	53

132N	AA59569R34N0062	1/16"	34	16	2	32	19	1,272	8
134N	AA59569R34N0109	7/64"	34	16	4	64	16	2,544	12
136N	AA59569R34N0125	1/8"	34	24	3	72	16	2,862	12
137N	Not on spec	9/64"	34	24	4	96	15	3,816	17
138N	AA59569R34N0171	11/64"	34	24	5	120	14	4,770	20
140N	Not on spec	3/16"	34	24	6	144	13	5,724	22
142N	Not on spec	1/4"	34	24	7	168	12	6,678	26
144N	Not on spec	3/8"	34	24	8	192	11	7,632	30
145N	AA59569R34N0375	3/8"	34	48	5	240	10	9,740	38
146N	AA59569R34N0500	1/2"	34	48	7	336	9	13,356	53
148N	Not on spec	5/8"	34	48	8	384	8	15,264	56
150N	Not on spec	11/16"	34	48	10	480	7	19,080	67
152N	AA59569R34N0781	25/32"	34	48	11	528	7	20,988	77
153N	Not on spec	13/16"	34	48	12	576	7	22,896	85
160N	AA59569R36N0031	1/32"	36	24	1	24	22	600	5
162N	AA59569R36N0062	1/16"	36	24	2	48	19	1,200	7
163N	AA59569R36N0078	5/64"	36	24	3	72	18	1,800	9
164N	AA59569R36N0109	7/64"	36	24	4	96	16	2,400	11
166N	AA59569R36N0125	1/8"	36	24	5	120	15	3,000	13
167N	AA59569R36N0156	5/32"	36	24	10	240	12	6,000	24
168N	AA59569R36N0171	11/64"	36	24	7	168	14	4,200	17
170N	AA59569R34N0203	13/64"	34	24	8	192	11	7,630	31
170/1N	AA59569R36N0203	13/64"	36	24	13	312	11	7,800	31
171N	AA59569R36N0250	1/4"	36	24	16	384	10	9,600	38
171/1N	AA59569R30N0281	9/32"	30	24	5	120	9	12,060	47
171/2N	AA59569R30N0375	3/8"	30	24	7	168	8	16,880	62
172N	AA59569R36N0375	3/8"	36	48	8	384	10	9,600	40
173N	AA59569R30N0437	7/16"	30	24	10	240	6	24,120	85
173/1N	AA59569R30N0500	1/2"	30	24	15	360	5	36,180	122
174N	AA59569R36N0500	1/2"	36	48	11	528	9	13,200	53

175N	AA59569R30N0562	9/16"	30	48	10	480	3	48,240	156
175/1N	AA59569R30N0656	21/32"	30	48	16	768	1	77,180	259
176N	AA59569R36N0781	25/32"	36	48	18	864	7	21,600	79
177N	AA59569R30N0875	7/8"	30	48	7	336	5	33,770	123
178N	AA59569R30N1000	1"	30	48	8	384	4	38,600	140
179N	AA59569R30N1125	1-1/8"	30	48	9	432	4	43,420	155
180N	Not on spec	1-1/4"	30	48	10	480	3	48,240	168
181N	AA59569R30N1375	1-3/8"	30	48	11	528	3	53,060	185
182N	AA59569R30N1500	1-1/2"	30	48	12	576	3	57,890	200
183N	AA59569R30N2000	2"	30	48	14	672	2	67,540	230
184N	Not on spec	2-1/4"	30	48	16	768	1	77,180	260

Cross Reference

8662

Search for Products

Search Term(s):

[Home](#) [About Us](#) [News](#) [Products](#) [Locations](#) [Contact Us](#)

© International Wire Group, All Rights Reserved. Site Built by [Brockett Creative Group, Inc.](#)