


[Home](#)
[About Us](#)
[News](#)
[Products](#)
[Locations](#)
[Contact Us](#)

Products

Browse Products

 Select Metal Type:

 Select Construction Category:

Tinned Copper (ASTM B33) > Multi-Layer Braids

TINNED COPPER MULTIPLE LAYERED BRAIDS

Part No.	Nominal Flat Width	Nominal Thickness	AWG of Individual Ends	No. of Layers	No. of Strands (Carriers) per Layer	No. of Wires per Strand	Total No. of Wires	Approx. AWG Equivalent	Nom. Circular Mills	Calculated Amperage	Approx. Shipping Weight (Lbs/1000 Ft)
290	1.125"	.270"	30	2	24	27	1,296	2/0	129,600	250	475
291	1.250"	.290"	30	2	24	32	1,536	3/0	153,600	290	560
292	1.250"	.300"	30	2	24	35	1,680	3/0	168,000	320	600
293	1.250"	.400"	30	3	24	32	2,304	4/0	230,400	385	825
294	1.375"	.510"	30	4	24	32	3,072	300 MCM	307,200	465	1,110
295	1.500"	.500"	30	3	24	47	3,384	325 MCM	338,400		1,105
296	2.125"	.290"	30	2	48	32	3,072	300	MCM		1,064
297	2.125"	.300"	30	3	48	35	5,040	500 MCM	504,000		1,700

Search for Products

 Search Term(s):

[Home](#)

[About Us](#)

[News](#)

[Products](#)

[Locations](#)

[Contact Us](#)

© International Wire Group, All Rights Reserved. Site Built by [Brockett Creative Group, Inc.](#)