

RETRACTILE CORDS: COMMUNICATION (SHIELDED & UNSHIELDED - MINIATURE)

BRIM MINIATURE COMMUNICATION CORDS -- UL APPROVED

RETRACTED Lengths: 1, 2 & 4 Ft. EXTENDED Lengths: 5,10 & 20 Ft.

Miniature in size. Suitable for compact equipment. All conductors 28 AWG 19/40 T.C., 100V & 1/2 AMP rating. Black Bryon™ jacket overall. OPER. TEMP.: - 20°C to +80°C. STD. PKG.: 6



BRIM No. 4Ft. +	Retracted 2Ft.	Lengths 1Ft. +	No. Cond.	AWG	Strand.	Nom.O.D. Coil	Nom.O.D. Cord
118-4++	118-2++	118-1++	2	28	19/40	1/2"	.150"
118/3-4++	118/3-2++	118/3-1++	3	28	19/40	1/2"	.155"
119-4++	119-2++	119-1++	4	28	19/40	1/2"	.160"
125-4++	125-2++	125-1++	5	28	19/40	9/16"	.170"
125/6-4++	125/6-2++	125/6-1++	6	28	19/40	5/8"	.185"
125/7-4++	125/7-2++	125/7-1++	7	28	19/40	5/8"	.190"
126-4++	126-2++	126-1++	8	28	19/40	5/8"	.200"
----	127-2	----	9	28	19/40	11/16"	.220"
----	127/10-2	----	10	28	19/40	3/4"	.230"
----	127/11-2	----	11	28	19/40	3/4"	.240"
----	127/12-2	----	12	28	19/40	7/8"	.250"
----	127/13-2	----	13	28	19/40	7/8"	.260"
----	127/15-2	----	15	28	19/40	1"	.270"
----	127/17-2	----	17	28	19/40	1"	.280"

+Also avail. in TPE insulation--cable O.D.'s slightly larger. ++PVC Constructions are UL approved.