


[Home](#)
[About Us](#)
[News](#)
[Products](#)
[Locations](#)
[Contact Us](#)

Products

Browse Products

 Select Metal Type:

 Select Construction Category:

Bare Copper > Flat Braid

BARE COPPER FLAT BRAID

Made in the same manner as AA59569 braids, although no Bare Copper Braids are listed on that specification. Flat Braid is typically used as a flexible and durable ground strap. The raw material meets ASTM B3 requirements.

Part No.	Nominal Flat Width	Nominal Thickness	AWG of Individual Ends	No. of Strands (Carriers)	No. of Wires per Strand	Total No. of Wires	Approx. AWG Equivalent	Nom. Circular Mills	Calculated Amperage	Approx. Shipping Weight (Lbs/1000 Ft)
221B	.025"	.015"	36	8	1	8	27	200	4	3
222B	.031"	.020"	36	16	1	16	24	400	6	4
223B	.046"	.020"	36	24	1	24	22	600	7	5
224B	.094"	.020"	36	16	3	48	19	1,200	11	7
225B	.093"	.031"	36	24	2	48	19	1,200	11	7
226B	.109"	.020"	36	16	4	64	18	1,800	16	8
229B	.125"	.020"	36	24	3	72	18	1,800	16	9
229/1B	.156"	.031"	36	24	4	96	16	2,400	19	11

230B	.187"	.020"	36	24	5	120	15	3,000	25	13
231B	.250"	.030"	36	24	7	168	14	4,200	32	17
231/1B	.250"	.046"	36	24	10	240	12	6,000	40	24
231/2B	.281"	.046"	36	24	13	312	11	7,800	46	31
232B	.375"	.030"	36	48	6	288	12	7,200	40	28
232/1B	.375"	.045"	30	24	5	120	9	12,060	60	47
233B	.625"	.030"	36	48	8	384	10	9,600	53	40
233/1B	.625"	.046"	36	48	11	528	9	13,200	62	53
233/2B	.500"	.030"	36	48	8	384	10	9,600	53	39
234B	.750"	.040"	36	48	18	864	7	20,800	88	79
235B	1.000"	.045"	36	48	18	864	7	20,800	85	75
236B	.812"	.045"	36	48	19	912	7	22,800	93	80
236/1B	.875"	.050"	36	48	22	1,056	6	26,400	105	95
237B	.750"	.040"	36	24	67	1,608	4	40,200	125	140
238B	1.625"	.080"	36	48	84	4,032	1/0	100,800	230	359
240B	.500"	.093"	30	24	10	240	6	24,120	90	85
242B	.625"	.093"	30	24	15	360	5	36,180	120	122
244B	.750"	.110"	30	24	20	480	3	48,000	145	170
246B	.875"	.120"	30	24	24	576	3	57,600	165	193
248B	.937"	.130"	30	24	26	624	2	62,400	170	210
250B	.937"	.130"	30	24	27	648	2	64,800	175	225
252B	1.000"	.140"	30	24	32	768	1	76,800	195	270
260B	.750"	.050"	30	48	5	240	6	24,000	93	88
262B	1.375"	.050"	30	48	7	336	5	33,770	100	123
264B	1.000"	.070"	30	48	8	384	4	38,400	120	137
266B	1.250"	.080"	30	48	10	480	3	48,000	145	168
268B	1.500"	.060"	30	48	11	528	3	53,060	145	185
270B	.875"	.090"	30	48	12	576	2	57,600	150	200
272B	1.375"	.090"	30	48	14	672	2	67,200	165	230
274B	1.500"	.100"	30	48	16	768	1	76,800	180	265

276B	1.625"	.110"	30	48	18	864	1	86,400	200	283
278B	1.375"	.120"	30	48	22	1,056	1/0	105,600	235	362
279B	1.750"	.130"	30	48	26	1,248	2/0	124,800	250	430
280B	2.000"	.130"	30	48	28	1,344	2/0	134,400	255	464
282B	2.000"	.140"	30	48	32	1,536	3/0	153,600	290	530
284B	2.000"	.150"	30	48	35	1,680	3/0	168,000	320	570
286B	2.375"	.175"	30	48	44	2,112	4/0	211,200	370	730
287B	3.000"	.190"	30	48	47	2,256	4/0	225,600	390	780
288B	2.500"	.190"	30	48	52	2,496	250 MCM	249,600	410	900

Part No.	Nominal Flat Width	Nominal Thickness
----------	--------------------	-------------------

Cross Reference

8662

Search for Products

Search Term(s):

[Home](#) [About Us](#) [News](#) [Products](#) [Locations](#) [Contact Us](#)

© International Wire Group, All Rights Reserved. Site Built by [Brockett Creative Group, Inc.](#)