


CG 100 PG POLYAMIDE CABLE GLANDS

PG thread

Liquid tight seal, fast and easy installation, wide clamping range, multi-purpose applications, easy handling.



Technical Details

Material	Polyamide 6
Seal	Chloroprene (CR)
Color	RAL 7001 (Gray)
	RAL 9005 (Black)
Protection Class	IP 68 - 5 Bar
Temperature Range	-20°C to +100°C permanent
	-30°C to +150°C intermittent
Flammability	V2 (According to UL 94)
Approvals	UL, UR, CSA

Part Number		Thread Type	Clamping Range Ø min-max		Thread Diameter (TD)		Wrenching Flats (SW)		Thread Length (TL)	Height (H)	UL ¹
Gray	Black		inches	mm	inches	mm	inches	mm			
PG											
PPG-7	PPB-7	PG 7	.118 - .256	3.0 - 6.5	0.492	12.5	0.591	15	0.315	0.866	UR
PPG-9	PPB-9	PG 9	.157 - .315	4.0 - 8.0	0.598	15.2	0.748	19	0.315	0.984	UR
PPG-11	PPB-11	PG 11	.197 - .394	5.0 - 10.0	0.732	18.6	0.866	22	0.315	1.102	UR
PPG-13	PPB-13	PG 13.5	.236 - .472	6.0 - 12.0	0.803	20.4	0.945	24	0.355	1.142	UL
PPG-16	PPB-16	PG 16	.394 - .551	10.0 - 14.0	0.886	22.5	1.063	27	0.394	1.220	UL
PPG-21	PPB-21	PG 21	.512 - .709	13.0 - 18.0	1.114	28.3	1.299	33	0.433	1.378	UL
PPG-29	PPB-29	PG 29	.709 - .984	18.0 - 25.0	1.457	37.0	1.654	42	0.433	1.575	UL
PPG-36	PPB-36	PG 36	.866 - 1.261	22.0 - 32.0	1.850	47.0	2.087	53	0.512	1.929	UL
PPG-42	PPB-42	PG 42	1.181 - 1.496	30.0 - 38.0	2.126	54.0	2.362	60	0.512	1.929	UL
PPG-48	PPB-48	PG 48	1.339 - 1.732	34.0 - 44.0	2.335	59.3	2.559	65	0.552	1.929	UL
PG with Reducer Bushings											
PPG-7R	PPB-7R	PG 7	.079 - .197	2.0 - 5.0	0.492	12.5	0.591	15	0.315	0.866	-
PPG-9R	PPB-9R	PG 9	.079 - .236	2.0 - 6.0	0.598	15.2	0.748	19	0.315	0.984	-
PPG-11R	PPB-11R	PG 11	.118 - .276	3.0 - 7.0	0.732	18.6	0.866	22	0.315	1.102	-
PPG-13R	PPB-13R	PG 13.5	.197 - .355	5.0 - 9.0	0.803	20.4	0.945	24	0.355	1.142	-
PPG-16R	PPB-16R	PG 16	.276 - .473	7.0 - 12.0	0.886	22.5	1.063	27	0.394	1.220	-
PPG-21R	PPB-21R	PG 21	.354 - .630	9.0 - 16.0	1.114	28.3	1.299	33	0.433	1.378	-
PPG-29R	PPB-29R	PG 29	.472 - .788	12.0 - 20.0	1.457	37.0	1.654	42	0.433	1.575	-
PPG-36R	PPB-36R	PG 36	.788 - 1.024	20.0 - 26.0	1.850	47.0	2.087	53	0.512	1.929	-
PPG-42R	PPB-42R	PG 42	.984 - 1.220	25.0 - 31.0	2.126	54.0	2.362	60	0.512	1.929	-
PPG-48R	PPB-48R	PG 48	1.142 - 1.378	29.0 - 35.0	2.335	59.3	2.559	65	0.552	1.929	-

¹ Additional UL approvals in progress
Locknut included