



Jacketed MC Connectors ServiceDrive® ASD/VFD

*For use with ServiceDrive® and
ServiceDrive Plus® Cable System*

Description & Features:

These patented connectors are designed exclusively to terminate ASD/VFD cables in control centers, panel boards, junction boxes and motor control enclosures.

Listings:

Class 1, Div. 2 and Class 2, Div. 1 & 2
CSA Standard: C22.2 #18.98
NEMA 4
IP65
Thread Type: NPT

Part Number	Wire Size	Hub Size	Set Screw Size
CONASD14/3	14 AWG 3 COND	3/4"	10/32 X 1/4"
CONASD12/3	12 AWG 3 COND	3/4"	10/32 X 1/4"
CONASD10/3	10 AWG 3 COND	3/4"	10/32 X 1/4"
CONASD8/3	8 AWG 3 COND	3/4"	10/32 X 1/4"
CONASD6/3	6 AWG 3 COND	1-1/4"	1/4-20 X 1/4"
CONASD4/3	4 AWG 3 COND	1-1/4"	1/4-20 X 1/4"
CONASD3/3	3 AWG 3 COND	1-1/4"	1/4-20 X 1/4"
CONASD2/3	2 AWG 3 COND	1-1/4"	1/4-20 X 1/4"
CONASD1/3	1 AWG 3 COND	1-1/4"	1/4-20 X 1/4"
CONASD1/03	1/0 AWG 3 COND	1-1/2"	1/4-20 X 1/4"
CONASD2/03	2/0 AWG 3 COND	1-1/2"	1/4-20 X 1/4"
CONASD3/03	3/0 AWG 3 COND	1-1/2"	1/4-20 X 1/4"
CONASD4/03	4/0 AWG 3 COND	2"	1/4-20 X 5/16"
CONASD250/3	250 MCM 3 COND	2"	1/4-20 X 5/16"
CONASD300/3	300 MCM 3 COND	2"	1/4-20 X 5/16"
CONASD350/3	350 MCM 3 COND	2-1/2"	5/16-18 X 3/8"
CONASD400/3	400 MCM 3 COND	2-1/2"	5/16-18 X 3/8"
CONASD500/3	500 MCM 3 COND	2-1/2"	5/16-18 X 3/8"
CONASD600/3	600 MCM 3 COND	3"	5/16-18 X 3/8"
CONASD750/3	750 MCM 3 COND	3"	5/16-18 X 3/8"