



## Tray Cable Connectors ServiceDrive® ASD/VFD

*Patented for use with ServiceDrive®  
and ServiceDrive Plus® Cable Systems*

### Description & Features:

These patented connectors are designed exclusively to terminate ASD/VFD cables in control centers, panel boards, junction boxes and motor control enclosures.

### Listings:

Class 1, Div. 2 and Class 2, Div. 1 & 2  
CSA Standard: C22.2 #18.98  
NEMA 4  
IP65  
Thread Type: NPT

| Part Number   | Wire Size      | Hub Size | Set Screw Size |
|---------------|----------------|----------|----------------|
| CONASDTC14/3  | 14 AWG 3 COND  | 3/4"     | 10/32 X 1/4"   |
| CONASDTC12/3  | 12 AWG 3 COND  | 3/4"     | 10/32 X 1/4"   |
| CONASDTC10/3  | 10 AWG 3 COND  | 3/4"     | 10/32 X 1/4"   |
| CONASDTC8/3   | 8 AWG 3 COND   | 3/4"     | 10/32 X 1/4"   |
| CONASDTC6/3   | 6 AWG 3 COND   | 3/4"     | 10/32 X 1/4"   |
| CONASDTC4/3   | 4 AWG 3 COND   | 1 "      | 1/4-20 X 1/4"  |
| CONASDTC3/3   | 3 AWG 3 COND   | 1 "      | 10/32 X 1/4"   |
| CONASDTC2/3   | 2 AWG 3 COND   | 1-1/4"   | 1/4-20 X 1/4"  |
| CONASDTC1/3   | 1 AWG 3 COND   | 1-1/4"   | 1/4-20 X 1/4"  |
| CONASDTC1/03  | 1/0 AWG 3 COND | 1-1/2"   | 1/4-20 X 1/4"  |
| CONASDTC2/03  | 2/0 AWG 3 COND | 1-1/2"   | 1/4-20 X 1/4"  |
| CONASDTC3/03  | 3/0 AWG 3 COND | 1-1/2"   | 1/4-20 X 1/4"  |
| CONASDTC4/03  | 4/0 AWG 3 COND | 1-1/2"   | 1/4-20 X 5/16" |
| CONASDTC250/3 | 250 MCM 3 COND | 2"       | 1/4-20 X 5/16" |
| CONASDTC300/3 | 300 MCM 3 COND | 2"       | 5/16-18 X 3/8" |
| CONASDTC350/3 | 350 MCM 3 COND | 2"       | 5/16-18 X 3/8" |
| CONASDTC400/3 | 400 MCM 3 COND | 2"       | 5/16-18 X 3/8" |
| CONASDTC500/3 | 500 MCM 3 COND | 2-1/2"   | 5/16-18 X 3/8" |
| CONASDTC600/3 | 600 MCM 3 COND | 2-1/2"   | 5/16-18 X 3/8" |
| CONASDTC750/3 | 750 MCM 3 COND | 3"       | 5/16-18 X 3/8" |