



## UL Listed Connectors Water Tight For Interlocked Armor Cable with Jacket

### Listings:

UL: Class I\* Group A, B, C and D  
Class II\* Group E, F and G  
Class III

\* Includes Division 1 and Division 2

### CONSTRUCTION

Suitable for industrial and commercial use.

Manufactured from 6061 copper-free aluminum.

A complete range of NPT (National Pipe Thread) sizes are available from 1/2" through 4". This accommodates armored cable type MC O.D. sizes from 0.38 - 4.33".

### DESCRIPTION & FEATURES:

These U.L. listed connectors are a one-piece body construction with a unique scroll design that can provide a 360 degree ground to armor.

This connector provides a fast and easy installation, eliminates internal components, prevents cable pullout and saves time and labor.

Copper AIA-PVC	Part Number	O.D. Range	Copper AIA-PVC	Part Number	O.D. Range	Copper AIA-PVC	Part Number	O.D. Range
14/2 AAP	CONW56	.500 - .560	10/3 AAP	CONW69	.620 - .690	1/04 AAP	CONW148	1.390 - 1.480
14/3 AAP	CONW56	.500 - .560	10/4 AAP	CONW76	.690 - .760	2/03 AAP	CONW148	1.390 - 1.480
14/4 AAP	CONW62	.560 - .620	10/5 AAP	CONW83	.760 - .830	2/04 AAP	CONW157	1.480 - 1.570
14/5 AAP	CONW69	.620 - .690	10/7 AAP	CONW83	.760 - .830	3/03 AAP	CONW157	1.480 - 1.570
14/7 AAP	CONW69	.620 - .690	10/9 AAP	CONW97	.900 - .970	3/04 AAP	CONW175	1.660 - 1.750
14/9 AAP	CONW76	.690 - .760	10/19 AAP	CONW118	1.110 - 1.180	4/03 AAP	CONW166	1.570 - 1.660
14/12 AAP	CONW83	.760 - .830	10/25 AAP	CONW139	1.320 - 1.390	4/04 AAP	CONW184	1.750 - 1.840
14/19 AAP	CONW104	.970 - 1.040	10/37 AAP	CONW157	1.480 - 1.570	250/3 AAP	CONW184	1.750 - 1.840
14/25 AAP	CONW104	.970 - 1.040	8/3 AAP	CONW76	.690 - .760	250/4 AAP	CONW202	1.930 - 2.020
14/37 AAP	CONW125	1.180 - 1.250	8/4 AAP	CONW83	.760 - .830	300/3 AAP	CONW202	1.930 - 2.020
12/2 AAP	CONW56	.500 - .560	6/3 AAP	CONW83	.760 - .830	300/4 AAP	CONW224	2.130 - 2.240
12/3 AAP	CONW62	.560 - .620	6/4 AAP	CONW97	.900 - .970	350/3 AAP	CONW213	2.020 - 2.130
12/4 AAP	CONW69	.620 - .690	4/3 AAP	CONW97	.900 - .970	350/4 AAP	CONW235	2.240 - 2.350
12/5 AAP	CONW69	.620 - .690	4/4 AAP	CONW104	.970 - 1.040	400/3 AAP	CONW224	2.130 - 2.240
12/7 AAP	CONW76	.690 - .760	3/3 AAP	CONW104	.970 - 1.040	400/4 AAP	CONW246	2.350 - 2.460
12/9 AAP	CONW83	.760 - .830	3/4 AAP	CONW111	1.040 - 1.110	500/3 AAP	CONW235	2.240 - 2.350
12/12 AAP	CONW90	.830 - .900	2/3 AAP	CONW111	1.040 - 1.110	500/4 AAP	CONW257	2.460 - 2.570
12/19 AAP	CONW104	.970 - 1.040	2/4 AAP	CONW125	1.180 - 1.250	600/3 AAP	CONW257	2.460 - 2.570
12/25 AAP	CONW111	1.040 - 1.110	1/3 AAP	CONW125	1.180 - 1.250	600/4 AAP	CONW285	2.710 - 2.850
12/37 AAP	CONW139	1.320 - 1.390	1/4 AAP	CONW139	1.320 - 1.390	750/3 AAP	CONW285	2.710 - 2.850
10/2 AAP	CONW62	.560 - .620	1/03 AAP	CONW139	1.320 - 1.390	750/4 AAP	CONW313	2.990 - 3.130

Armor Cables