

COPPERFIELD® UL STYLE 1007/1569/1581

CSA AWM I A/B (PVC)

- CONDUCTORS:**
- 26 AWG - 12 AWG Stranded Tinned Copper per ASTM B-33
 - 24 AWG - 16 AWG Solid Tinned Copper per ASTM B-33
 - 24 AWG - 16 AWG Stranded, Topcoated Copper per ASTM B-33

- INSULATION:**
- Color-Coded Polyvinyl Chloride (PVC)

- TEMPERATURE RANGE/
VOLTAGE RATING:**
- UL 1007, UL 1581: 80°C/300V
 - UL 1569: 105°C/300V

- FLAME COMPLIANCES:**
- UL VW-1
 - CSA FT-1

- INDUSTRY APPROVALS:**
- UL Standard 758 - Styles 1007, 1569, & 1581
 - CSA AWM I A/B, TR-64

- STANDARD COLORS:**
- Black
 - White
 - Red
 - Orange
 - Yellow
 - Green
 - Blue
 - Brown
 - Gray
 - Violet
 - Green/Yellow

- OPTIONS:**
- Stripes available upon request (minimums may apply)
 - Other copper constructions available upon request (minimums may apply)



HOOK-UP WIRE / APPLIANCE WIRE

Part Number	Gauge	Stranding	Nominal Wall		Nominal OD		UL Style	CSA Style	Weight	
			in.	mm.	in.	mm.			lbs./mft	kg/km
Stranded Tinned Copper										
F26002	26	7/34	0.016	0.41	0.050	1.27	1007/1569	AWM/TR64	1.8	3
F24002	24	7/.0076	0.016	0.41	0.057	1.45	1007/1569	AWM/TR64	2.5	4
F22021	22	7/.0096	0.016	0.41	0.062	1.57	1007/1569	AWM/TR64	3.3	5
F20030	20	10/30	0.016	0.41	0.067	1.70	1007/1569	AWM/TR64	4.5	7
F18041	18	16/30	0.016	0.41	0.079	2.01	1007/1569	AWM/TR64	6.8	10
F16025	16	26/30	0.016	0.41	0.091	2.31	1007/1569	AWM/TR64	10.2	15
F14028	14	41/30	0.016	0.41	0.110	2.79	1569/1581	AWM/TR64	15.7	23
F12035	12	65/30	0.016	0.41	0.123	3.12	1569/1581	AWM I A/B	23.1	34
Solid Tinned Copper										
F24016	24	SOLID	0.016	0.41	0.052	1.32	1007/1569	AWM/TR64	2.5	4
F22020	22	SOLID	0.015	0.38	0.062	1.57	1007/1569	AWM/TR64	3.3	5
F20029	20	SOLID	0.015	0.38	0.067	1.70	1007/1569	AWM/TR64	4.5	7
F18039	18	SOLID	0.016	0.41	0.079	2.01	1007/1569	AWM/TR64	6.8	10
F16376	16	SOLID	0.016	0.41	0.091	2.31	1007/1569	AWM/TR64	10.2	15
Stranded, Topcoated Copper										
F24013	24	7/32	0.016	0.41	0.057	1.45	1007/1569	AWM/TR64	2.5	4
F22017	22	7/30	0.016	0.41	0.062	1.57	1007/1569	AWM/TR64	3.3	5
F20028	20	10/30	0.016	0.41	0.067	1.70	1007/1569	AWM/TR64	4.5	7
F18037	18	7/.0152	0.016	0.41	0.079	2.01	1007/1569	AWM/TR64	6.8	10
F16377	16	26/30	0.016	0.41	0.091	2.31	1007/1569	AWM/TR64	10.2	15

Dimensions and weights are nominal and are subject to industry tolerances unless otherwise noted.

See page 127 for Ordering and Color Code information.



Coleman Cable Inc.
800.323.9355 • www.colemancable.com