

COPPERFIELD® UL STYLE 3340/3374

CSA CL 1503 (EPDM)

HOOK-UP WIRE / APPLIANCE WIRE



CONDUCTORS: • 18 AWG - 4/0 AWG Stranded Tinned Copper per ASTM B-33

INSULATION: • Color-Coded Ethylene Propylene (EPDM)

**TEMPERATURE RANGE/
VOLTAGE RATING:** • UL 758: 125°C/600V Flexing, 150°C/600V Non-Flexing
• CSA AWM: 125°C/600V
• CSA CL 1503 (150°C)

FLAME COMPLIANCES: • CSA FT-2

INDUSTRY APPROVALS: • UL Standard 758 - Styles 3340/3374
• CSA AWM I A/B, CL 1503

STANDARD COLORS: • Black • Orange • Blue
• White • Yellow
• Red • Green

OPTIONS: • Other colors & stripes available upon request (minimums may apply)
• Other copper constructions available upon request (minimums may apply)

Part Number	Gauge	Stranding	Nominal Wall		Nominal OD		Weight	
			in.	mm.	in.	mm.	lbs./mft	kg/km
F18176	18	16/30	0.045	1.14	0.140	3.56	12.0	18
F16103	16	26/30	0.045	1.14	0.153	3.89	17.0	25
F14168	14	41/30	0.045	1.14	0.168	4.27	22.0	33
F12062	12	65/30	0.045	1.14	0.184	4.67	31.0	46
F10024	10	105/30	0.045	1.14	0.212	5.38	46.0	68
F08036	8	84/29	0.060	1.52	0.293	7.44	79.0	118
F06101	6	133/27	0.060	1.52	0.335	8.51	112.0	167
F04045	4	133/25	0.060	1.52	0.365	9.27	168.0	250
F02015	2	133/23	0.060	1.52	0.435	11.05	264.0	393
F01034	1	259/25	0.080	2.03	0.532	13.51	323.0	481
F1T029	1/0	259/24	0.080	2.03	0.591	15.01	400.0	595
F2T024	2/0	259/23	0.080	2.03	0.625	15.88	492.0	732
F3T022	3/0	259/22	0.080	2.03	0.685	17.40	590.0	878
F4T025	4/0	259/21	0.080	2.03	0.745	18.92	743.0	1106

Dimensions and weights are nominal and are subject to industry tolerances unless otherwise noted.

See page 127 for Ordering and Color Code information.



Coleman Cable Inc.
800.323.9355 • www.colemancable.com