

COPPERFIELD® UL STYLE 1011/1015/1028/1032/ 1230/1231/1335/1344 UL BC-5W2/MTW/THHW CSA AWM I A/B & TEW (PVC)

HOOK-UP WIRE / APPLIANCE WIRE



CONDUCTORS: • 22 AWG - 8AWG Stranded Tinned Copper per ASTM B-33
• 22 AWG - 10 AWG Solid Tinned Copper per ASTM M-33

INSULATION: • Color-Coded Polyvinyl Chloride (PVC)

**TEMPERATURE RANGE/
VOLTAGE RATING:** • UL 1011/1015/1028/BC-5W2: 105°C/600V
• UL MTW: 90°C/600V
• CSA AWM I A/B & TEW: 105°C/600V

FLAME COMPLIANCES: • UL VW-1
• CSA FT-1

INDUSTRY APPROVALS: • UL Standard 758 - Styles 1011/1015/1028/1032/1230/1231/1335/1344
• UL Standard 1063 - MTW
• UL Standard 1426 - BC-5W2: 16 AWG - 8 AWG
• CSA AWM I A/B & TEW
• UL THHW
• UL CT Tray Rated
• SAE J378

STANDARD COLORS: • Black • Orange • Blue • Violet
• White • Yellow • Brown • Green/Yellow
• Red • Green • Gray

OPTIONS: • Stripes available upon request (minimums may apply)
• Other copper constructions available upon request (minimums may apply)

Part Number	Gauge	Stranding	Nominal Wall		Nominal OD		Weight	
			in.	mm.	in.	mm.	lbs./mft	kg/km
UL Styles 1011/1015/1032/1230/1335								
F22027	22	7/0096	0.030	0.76	0.091	2.31	5.5	8
F20037	20	10/30	0.030	0.76	0.099	2.51	7.1	11
F18054	18	16/30	0.030	0.76	0.106	2.69	9.3	14
F22035	22	Solid	0.030	0.76	0.091	0.094	5.5	8
F20036	20	Solid	0.030	0.76	0.099	0.096	7.1	11
F18109	18	Solid	0.030	0.76	0.106	0.102	9.3	14
F16067	16	Solid	0.030	0.76	0.117	0.112	12.9	19
F14062	14	Solid	0.030	0.76	0.132	0.130	18.4	27
UL Styles 1011/1015/1032/1230/1335 & BC-5W2								
F16032	16	26/30	0.030	0.76	0.117	2.97	12.9	19
F10192	10	Solid	0.030	0.76	0.175	4.45	40.6	60
UL Styles 1011/1015/1032/1230/1335 & BC-5W2/THHW								
F14037	14	41/30	0.030	0.76	0.132	3.35	18.4	27
F12024	12	65/30	0.030	0.76	0.151	3.84	26.9	40
F10012	10	105/30	0.030	0.76	0.175	4.45	40.6	60
UL Styles 1011/1028/1231/1344 & UL BC-5W2/THHW								
F08010	8	133/29	0.045	1.14	0.252	6.40	72.0	107
UL Styles 1028/1032/1232/1283/1346 & UL BC-5W2/THHW								
F08115	8	133/29	0.060	1.52	0.295	7.49	78.0	116

Dimensions and weights are nominal and are subject to industry tolerances unless otherwise noted.

See page 127 for Ordering and Color Code information.



Coleman Cable Inc.
800.323.9355 • www.colemancable.com