

COPPERFIELD® UL STYLE 1061

CSA AWM I A/B (S-R PVC)

HOOK-UP WIRE / APPLIANCE WIRE



CONDUCTORS: • 26 AWG - 16 AWG Stranded Tinned Copper per ASTM B-33

INSULATION: • Color-Coded Semi-Rigid Polyvinyl Chloride (S-R PVC)

**TEMPERATURE RANGE/
VOLTAGE RATING:** • UL 1061: 80°C/300V
• CSM AWM I A/B: 80°C/300V
• MIL-W-16878/1 Type B: 105°C/600V

FLAME COMPLIANCES: • UL VW-1
• CSA FT-1

INDUSTRY APPROVALS: • UL Standard 758 - Style 1061
• CSA AWM I A/B
• MIL-W-16878/1 TYPE B

STANDARD COLORS: • Black • Orange • Blue • Violet
• White • Yellow • Brown • Green/Yellow
• Red • Green • Gray

OPTIONS: • Stripes available upon request (minimums may apply)
• Other copper constructions available upon request (minimums may apply)

Part Number	Gauge	Stranding	Nominal Wall		Nominal OD		Weight	
			in.	mm.	in.	mm.	lbs./mft	kg/km
F26001	26	7/34	0.009	0.23	0.038	0.97	1.4	2
F24001	24	7/.0076	0.009	0.23	0.045	1.14	2.9	4
F22014	22	7/.0096	0.009	0.23	0.051	1.30	2.8	4
F20059	20	10/30	0.009	0.23	0.058	1.47	4.0	6
F18032	18	16/30	0.009	0.23	0.067	1.70	6.1	9
F16024	16	26/30	0.009	0.23	0.078	1.98	9.3	14

Dimensions and weights are nominal and are subject to industry tolerances unless otherwise noted.

See page 127 for Ordering and Color Code information.



Coleman Cable Inc.
800.323.9355 • www.colemancable.com