



SPECIFICATIONS

Frequency Range:	2.0 - 18.0 GHz
Coupling:	6.0 ± 1.00 dB
Insertion Loss ¹ :	1.00 dB Max
Coupling Flatness:	± 0.50 dB Max
Directivity 2.0 - 12.0 GHz:	15 dB Min
Directivity 12.0 - 18.0 GHz:	12 dB Min
VSWR:	1.50:1 Max
Input Power ² :	4 Watts Max
Connector Type:	SMA

Notes:

- Does not include coupling loss.
- For load VSWR better than 1.20:1

PULSAR MICROWAVE CORPORATION

PULSAR MICROWAVE CORPORATION
48 INDUSTRIAL WEST, CLIFTON NJ 07012
TEL: 973-779-6262 FAX: 973-779-2727
WWW.PULSARMICROWAVE.COM

DESCRIPTION :

Directional Coupler

MODEL NO. :

CS06-15-436/13

DIMENSIONS ARE IN INCHES
DECIMAL TOLERANCE:
2 PLACE ± .02
3 PLACE ± .010

SIZE
A

CAGE CODE :
0HR85

REV CODE :

SCALE : N / A

ALL SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE AT ANY TIME

SHEET 1 OF 1