

## **PRODUCT SPECIFICATION**

Controlled Document - Engineering Drive

CATALOG NUMBER: DESCRIPTION:		See table below Polar/ Solar Plus SEOW extension cord with power indicator light in the cord connector			
APPROVALS:		UL Listed and CSA Certified Outdoor Use Cord Set			
CONSTRUCTION F	PARAMETERS:				
Conductor:		See table below			
Jacket material:		TPE, yellow			
Overall cable O.D. (nom):		See table below			
Cord rating:		Extra Hard Usage per the National Electrical Code			
Cable legend type:		Indent print			
Attachment plug configuration: Cord connector configuration:		NEMA 5-15P NEMA 5-15R			
Plug and connector material:		Clear PVC, with neon power indicator lamp in the cord connector			
Flug and connector material.			Clear PVC, with neon power indicator lamp in the cord connector		
					)
ELECTRICAL PRO	PERTIES:				
Cable temperature rating:		-50 to +90 °C			
Cable tempera	ature rating:	-50 to +90 °C			
Cable tempera Nominal operat		-50 to +90 °C 125 VAC			
	ing voltage:				
Nominal operat Maximum operat	ing voltage: ting current:	125 VAC See table below			
Nominal operat	ing voltage:	125 VAC	Cable O.D. (nom)	Current rating	
Nominal operat Maximum operat Catalog number 01567	ing voltage: ting current: Length 25 ft	125 VAC See table below Conductor		v	
Nominal operat Maximum operat Catalog number 01567 01568	ing voltage: ting current: Length 25 ft 50 ft	125 VAC See table below	Cable O.D. (nom) 0.516 in.	15A	
Nominal operat Maximum operat Catalog number 01567 01568 01569	ing voltage: ting current: Length 25 ft 50 ft 100 ft	125 VAC See table below Conductor		v	
Nominal operat Maximum operat Catalog number 01567 01568 01569 01767	ing voltage: ting current: Length 25 ft 50 ft 100 ft 25 ft	125 VAC See table below Conductor 14/3 41/30 BC	0.516 in.	15A 13A	
Nominal operat Maximum operat Catalog number 01567 01568 01569 01767 01768	ing voltage: ting current: Length 25 ft 50 ft 100 ft 25 ft 50 ft	125 VAC See table below Conductor		15A	
Nominal operat Maximum operat Catalog number 01567 01568 01569 01767	ing voltage: ting current: Length 25 ft 50 ft 100 ft 25 ft	125 VAC See table below Conductor 14/3 41/30 BC	0.516 in.	15A 13A	
Nominal operat Maximum operat Catalog number 01567 01568 01569 01767 01768 01769	ing voltage: ting current: Length 25 ft 50 ft 100 ft 25 ft 50 ft 100 ft	125 VAC See table below Conductor 14/3 41/30 BC 12/3 65/30 BC	0.516 in. 0.585 in	15A 13A	
Nominal operat Maximum operat Catalog number 01567 01568 01569 01767 01768 01769 This product compli	ing voltage: ting current: Length 25 ft 50 ft 100 ft 25 ft 50 ft 100 ft es with Europea	125 VAC See table below Conductor 14/3 41/30 BC 12/3 65/30 BC	0.516 in. 0.585 in EC (RoHS)	15A 13A 15A	
Nominal operat Maximum operat Catalog number 01567 01568 01569 01767 01768 01768 01769 This product complia The information presented	ing voltage: ting current: Length 25 ft 50 ft 100 ft 25 ft 50 ft 100 ft es with Europea I here is, to the best	125 VAC See table below Conductor 14/3 41/30 BC 12/3 65/30 BC an Directive 2002/95/ of our knowledge, true and	0.516 in. 0.585 in	15A 13A 15A onditions of use are	

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.

CUSTOMER APPROVAL:	Approved by:	Date:
	Title:	