



# Heyco® Custom Turn-2-Lock Cord and Plug Sets

Male Configurations for 277 V, 15 Amp Applications

**UL** <sup>c</sup> <sub>us</sub> Listed for Use in the U.S. and Canada Under File E217650

- Consult Heyco for special lengths, applied Terminations and Strain Reliefs, and **other custom configurations not shown**. Turn-2-Lock can be supplied with a Strain Relief, Metallic or Non-Metallic Cordgrip, and/or a Ring or other Terminal(s) already attached, to **save time** and **reduce cost** in your assembly process.
- Popular 125, 250, 277, 347, and 480 Volt; with 15, 20 and 30 Amp NEMA Configurations are available.
- We offer 12” to 15+ feet Turn-2-Lock Whips in both Male and Female NEMA configurations.
- **Applications:** For use in highbay and lowbay lighting; display cases; and commercial cooking, laundry, construction, and other specialty equipment where the possibility of the male and female ends of the plug becoming easily disconnected is not an option.
- Standard colors are Black and White. Consult Heyco for custom colors.

DESCRIPTION Volts-Amps	Type	WIRE		Length A* in.	PART NO.	ROJ	Strip	Ring	Strain Relief	
		Gauge AWG-Cond	Color			B in.	Length C in.	Terminal Part No. **	***	D in.
<b>NEMA L7-15P, 277 Volts, 15 Amps, 16 Gauge</b>										
T2L 277V-15A	SE00W	16-3	Black	36.0	S7630	2.5	1/2	8125		
				46.0	S7630S	5	1/2			
				47.0	S7630F	6	5/8	-		
				48.0	S7630CC	7	1/2			
				70.0	S7630T	5	1/2			
				72.0	S7630FF	2.5	5/8	-		
					S7630G	2.5	1/2	8125		
				80.5	S7630BS	3	3/8	-		
					S7630BF	2.5	1/2	-		
				84.0	S7630EE	7	1/2	-		
					S7630H	3	1/2	8125		
					S7630HH	6	5/8	-		
				96.0	S7630I	2.5	1/2	8125		
					S7630CB	5	1/2	-		
					S7630U	5	1/2	-		
				120.0	S7630AZ	2.5	1/2	-	1859	3.5
					S7630BA S7630KK	2.5 7	1/2	-		
				131.0	S7630BX	6	5/8	8125		
					S7630Z	6	5/8	-		
				132.0	S7630AN	2.5	1/2	8125		
142.0	S7630V	5	1/2	-						
144.0	S7630M	2.5	1/2	8125						
156.0	S7630GG	7	1/2	-						
180.0	S7630P	2.5	1/2	8125						
T2L 277V-15A	SE00W	16-3	White	36.0	S7631	2.5	1/2	8125	-	-
					S7631BQ	5	1/2	-	-	-
					S7631E	5.5	1/2	8125	1859	6.5
					S7631CD	5.5	1/2	8123	1860	
					S7631W	2.5	5/8	-	-	-
				42.0	S7631D	3	1/2			
					S7631F	6	5/8	-		
					S7631CC	7	1/2			
					S7631AF	2.5	5/8			
				72.0	S7631BN	5	1/2	8145	1865	6
					S7631FF	2.5	5/8	-	-	-
					S7631G	2.5	1/2	8125	-	-
				78.0	S7631AU	4	1/2	8125	-	-
					S7631CE	5.5	1/2	8123	1860	
					S7631C	4	1/2	8125	1859	6

\* Consult Heyco for custom lengths, applied Ring Terminals and applied Strain Relief devices.  
 \*\* For additional Heyco Terminals see pages 8-15 thru 8-20.  
 \*\*\* For additional Heyco Liquid Tight and Strain Relief Devices, see Sections 3 & 4.