



CONDUCTOR SPECIFICATIONS:

CONDUCTOR SIZE: 3 X 18 AWG
 DESCRIPTION: SJT
 FLAME RATING: VW1
 JACKET TYPE: OIL RESISTANT PVC
 TYPICAL STRANDING: 41/34AWG
 NOMINAL O.D.: .300-.325"
 CURRENT RATING: 10A
 VOLTAGE RATING: 300V
 MAX. TEMPERATURE: 60°C/CSA
 COLOR: BLACK
 RoHS COMPLIANT
 WIRE COLORS: NORTH AMERICAN

CONNECTOR SPECIFICATIONS:

STANDARD: IEC 320 STANDARD SHEET C13
 MATERIALS: PVC MOLDING
 FOR USE AT 10-20A/125VAC

DESCRIPTION:

UL LISTED AND CSA CERTIFIED TYPE SJT
 GENERAL PURPOSE, HEAVY DUTY FLEXIBLE
 CORD.

WIRING TOLERANCE
 OVERALL LENGTHS ONLY!
 .X = +/- .35"
 .XX = +/- .25"
 .XXX = +/- .13"

revisions			
no.	e.c.n.	date	by
P1		11/12/12	CPK

	tolerances: .x ±.030 .xx ±.015 .xxx ±.005	used on:
	angles: ±.5°	SEE VANTAGE
1780 EXECUTIVE DRIVE, P.O. BOX 84 OCONOMOWOC, WI 53066 (262) 567-4990 FAX (262) 953-5504	part name: POWER CORD 18/3 SJT 9'10" ROJ/C13	
material: ~	drawn by: CPK	scale: 1:1
Part must be free of welding scale and slag, sharp edges or corners, and burrs.	checked:	date: 10/22/12
		size: B
		drawing no.: PCD-00020
		rev.: P1

This material is the property of Bruno Independent Living Aids, Inc. No rights are granted to use such material for any purpose other than (1) product evaluation or maintenance, or (2) the furnishing of services to Bruno Independent Living Aids, Inc.